


# Pos-E-Kon®

NOTES:

1. CONNECTOR PINS ARE INSTALLED USING THE CT610 HAND TOOL.
  2. PINS ARE USED IN "A" AND "b" SIZE FOR MALE AND FEMALE INSERTS FOR CRIMP CONTACTS.
  3. PIN MATERIAL: BRASS  
FINISH: SILVER PLATING  
DIMENSIONS IN ( ) ARE MILLIETERS
- FOR CAT NO. PC 600 -  
MATERIAL: STEEL  
FINISH: SILVER PLATE 0.5 (MICRONS)

Cat No.	FIG.	Wire Size (AWG)
MP1800	1	18 [0.75 mm <sup>2</sup> ]
MP1600	1	16 [1.5 mm <sup>2</sup> ]
MP1400	1	14 [2.5 mm <sup>2</sup> ]
FP1800	2	18 [0.75 mm <sup>2</sup> ]
FP1600	2	16 [1.5 mm <sup>2</sup> ]
FP1400	2	14 [2.5 mm <sup>2</sup> ]
PC600	5	-----
MP2000	1	20 [0.50 mm <sup>2</sup> ]
FP2000	2	20 [0.50 mm <sup>2</sup> ]

www.tnb.com

REVISIONS	GENERAL NOTES	DESCRIPTION:			 A Member of the ABB Group
0 SEE ERN ( ) FOR APPROVAL SIGNATURES & RELEASE DATE. PROJECT NO:	1. ALL DIMENSIONS ARE FOR REFERENCE ONLY. 2. DIMENSIONS IN BRACKETS [ ] ARE IN METRIC UNITS.	<h2>CONNECTOR PINS</h2>			
		ORIGINAL PROJECT NO / (ERN NO) <b>SD50978 / ( 2016625 )</b>	SHEET NO: <b>1 OF 1</b>	REV. NO: <b>0</b>	