

Straight Blade Devices

15A 125V, 2 Pole, 3 Wire Grounding

Special Combination Duplex Receptacles

HUBBELL

Ordering Information

Description	Device Color	UPC Number	Catalog Number
Ivory nylon face, 2 circuit, back and side wired	Ivory	783585435428	HBL5292I

Listings

Certified to CSA, C22.2, No. 42 file 285
UL Listed to UL498 File E2186

Specifications

Face	Nylon
Base	Reinforced PET
Face Style	Finder Groove

Performance

Electrical

Current Interrupting	Certified for current interrupting at full rated current
Dielectric Voltage	Withstands 2,000V minimum

Mechanical

Product Identification	Ratings are a permanent part of the device
Terminal Accommodation	#14-#10 AWG copper stranded or solid conductor only
Terminal Identification	Terminals identified in accordance with UL 498 and CSA

Environmental

Flammability	UL 94 V-2 or better
Operating Temperatures	Maximum continuous 75°C; minimum -40°C (w/o impact)



Complementary Products

Wallplate or Weatherproof Cover Duplex Opening

Online Resources

eCatalog
Installation Instructions

Dimensions in Inches (mm)

Hubbell Wiring Device-Kellems • Hubbell Incorporated (Delaware) • 40 Waterview Drive • Shelton, CT 06484

Phone (800) 288-6000 • Fax (800) 255-1031 • Specifications subject to change without notice.

