



FS Spacer Clamp, Snap Close – FS24 (553550)



- Provides support for nVent ERIFLEX Flexibar and insulated braided conductors without damaging the insulation
- Ensures correct spacing for optimum cooling
- Supports up to four conductors in parallel
- Easy to install
- Halogen free
- RoHS compliant



| | |
|-----------------------------|---------------|
| Part Number | FS24 |
| Article Number | 553550 |
| Material | Polyamide |
| Working Temperature | -40 to 266 °F |
| Flammability Rating | UL® 94HB |
| Conductor Width | 0.95" Max |
| Height (H) | 2.638" |
| Length (L) | 1.18" |
| Hole Size (HS) | 0.27" |
| Unit Weight | 0.03 lb |
| Certifications | RoHS UR |
| Standard Packaging Quantity | 25 pc |
| UPC | 78285644978 |
| EAN-13 | 3479775535500 |

Recommended distance between supports is 400 mm (15 3/4").

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2020 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.