


Tinned Aluminum Earthing and Neutral Busbar – EB4AL (568711)



Earthing and Neutral Busbars are used to connect several earthing conductors within a panel and can be used in a variety of different applications such as switchgear and control equipment, electrical equipment, for wind and solar power generation and data centers.

- Tinned aluminum bar allows for copper or aluminum conductor connections
- Use to connect several earthing conductors
- Chamfered holes allow for easy connections
- Tin plating is corrosion resistant
- Rigid bar
- Can be fixed using IRS Angle Support Bracket, DMH Metallic Spacer or DH Distance Holder and Spacer
- Quick and easy installation
- RoHS compliant



| | |
|-----------------------|-----------------------------------|
| Part Number | EB4AL |
| Article Number | 568711 |
| Material | Aluminum |
| Finish | Tinned |
| Certification Details | UL® 467 |
| Number of Connections | 4 |
| Number of Holes | 6 |
| Conductor Size, IEC | 2.5 - 16 mm ² Stranded |
| Conductor Size, UL | #14 - #4 Stranded |
| Max Current Rating | 85 A |
| Height (H) | 0.44" |
| Width (W) | 1.88" |
| Depth (D) | 0.31" |
| Unit Weight | 0.013 lb |
| Certifications | cULus RoHS |

| | |
|-----------------------------|---------------|
| Part Number | EB4AL |
| Standard Packaging Quantity | 20 pc |
| UPC | 78285695249 |
| EAN-13 | 0782856952497 |

UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2020 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.