

product type designation

Reader RF1070R USB/RS232

SIMATIC RF1000 Access control reader RF1070R; ISO 14443 A/B Mifare, ISO15693 Legic Prime; Legic Advant USB port; RS 232 interface; IP65 front, -25 to +55 °C; 90 x 62 x 25 mm LxWxH; with integrated antenna; incl. 1.8 m USB connecting cable



suitability for operation

Legic, ISO 15693 and ISO 14443 A/B transponder, for connecting to PC and control systems

radio frequencies

operating frequency / rated value

13.56 MHz

range / maximum

30 mm; Range is dependent on transponder type: observe <http://support.automation.siemens.com/WW/view/en/67384964>

transfer rate / with radio transmission / maximum

106 kbit/s

product feature / multitag-capable

Yes

electrical data

transfer rate / at the point-to-point connection / serial / maximum

115.2 kbit/s

interfaces

standard for interfaces / for communication

USB 2.0, RS232

type of electrical connection

1.8 m connecting cable with USB 2.0 type A connector or RS232 connecting cable

mechanical data

material

PC-GF

color

Ti gray

tightening torque / of the screw for securing the equipment / maximum	1.5 N·m
mounting distance / relating to metal surfaces / recommended / minimum	0 mm

supply voltage, current consumption, power loss

supply voltage	
<ul style="list-style-type: none"> • at DC / rated value 	5 V
<ul style="list-style-type: none"> • at DC 	4.6 ... 5.25 V

ambient conditions

ambient temperature	
<ul style="list-style-type: none"> • during operation 	-25 ... +55 °C
<ul style="list-style-type: none"> • during storage 	-25 ... +55 °C
<ul style="list-style-type: none"> • during transport 	-25 ... +55 °C
protection class IP	IP65, on front after cabinet installation, IP20 rear
shock resistance	EN 60721-3-7 Class 7 M2
shock acceleration	300 m/s ²
vibrational acceleration	50 m/s ²

design, dimensions and weights

width	90 mm
height	62 mm
depth	23.5 mm
net weight	0.12 kg
fastening method	4 M4 screws for cabinet installation

product features, product functions, product components / general

display version	3-color LED
product feature / silicon-free	Yes

standards, specifications, approvals

certificate of suitability	Radio according to R&TTE guidelines EN300 330 and EN 301489, FCC, cULus
certificate of suitability	
<ul style="list-style-type: none"> • IECEx 	Yes

accessories

accessories	Card holder, USB cable 0.5 m, RS232 connector
-------------	---

further information / internet-Links

Internet-Link	
<ul style="list-style-type: none"> • to website: Selector TIA Selection Tool 	https://support.industry.siemens.com/cs/ww/en/view/67384964
<ul style="list-style-type: none"> • to website: Industrial communication 	http://www.siemens.com/ident/rfid
<ul style="list-style-type: none"> • to website: Industry Mall 	https://mall.industry.siemens.com
<ul style="list-style-type: none"> • to website: Information and Download Center 	http://www.siemens.com/industry/infocenter
<ul style="list-style-type: none"> • to website: Image database 	http://automation.siemens.com/bilddb

- to website: CAx-Download-Manager
- to website: Industry Online Support

<http://www.siemens.com/cax>

<https://support.industry.siemens.com>

last modified:

10/20/2020