

ODV-3-460280-3012-MN

Optidrive Eco VFD Datasheet

18.5 kW (25 HP), 28 A, 500-600 V, 3PH
IP20 Variable Frequency Drive with TFT Display



Input Ratings

Supply Voltage	500-600 V
Input Phases	3
Supply Current Continuous	34 A
Supply Fuse or MCB (Type B)	40 A

Output Ratings

Motor Output Rating	18.5 kW (25 HP)
Output Voltage	0 – Supply Voltage
Output Current	28 A

Cable Information

Max Supply Cable Size	16 mm ² (0.02 sq in)
Max Motor Cable Size	16 mm ² (0.02 sq in)
Max Motor Cable Length	100 m (328 ft)

Factory Build Options

EMC Filter	No Internal EMC
Brake Transistor	No Brake Transistor
Enclosure	IP20
Display	TFT Display
PCB Coating	Standard


Dimensions

Size	4
Height	418 mm (16.46 in)
Width	160 mm (6.3 in)
Depth	240 mm (9.45 in)
Weight	10.4 kg (22.93 lbs)
Fixings	-

Packaged Dimensions

Height	340 mm (13.39 in)
Width	280 mm (11.02 in)
Depth	560 mm (22.05 in)
Weight	12.4 kg (27.34 lbs)



 **Buy this drive or get more information**
Find your local sales partner on invertekdrives.com

