



Overview

| | |
|-----------|------------------------------|
| Lead time | Usually Ships within 2 Weeks |
|-----------|------------------------------|

General

| | |
|-------------------------------------|--------------------------------------|
| Provided equipment | Installation guide USB cable |
| Product web sub-family | Cloud-enabled monitoring |
| Performance multiplier | 1 |
| Number of tare power | 30 W |
| Number of power module free slots | 0 |
| Number of power module filled slots | 0 |
| Redundant | No |
| Size UPS version | Internetworking Server Telecom |
| UPS size | S |
| Value multiplier | 5 |

Physical

| | |
|---------------------|------------------------|
| Cable length | 6 ft (1.83 m) |
| Color | Black |
| Maximum Depth | 17.28 in (43.9 cm) |
| Maximum Height | 8.62 in (21.9 cm) |
| Mounting location | Front |
| Mounting preference | No preference |
| Net Weight | 54.23 lb(US) (24.6 kg) |
| Mounting mode | Not rack-mountable |
| Two post mountable | 0 |

| | |
|----------------|-------------------|
| USB compatible | Yes |
| Maximum Width | 6.73 in (17.1 cm) |

Input

| | |
|-------------------------|-------------------------------------|
| Input Frequency | 50/60 Hz +/- 3 Hz auto-sensing |
| Plug standard | NEMA 5-15P |
| Efficiency at full load | 75...154 V adjustable 82...144 V |
| Other Input Voltages | 110 V 125 V |
| Number of cables | 1 |
| Nominal Input Voltage | 120 V |

Output

| | |
|----------------------------------|---|
| Kw Rating | 1000 W |
| Max Configurable Power (Watts) | 1000 W |
| Harmonic distortion | Less than 5% |
| Output frequency | 50/60 Hz +/- 3 Hz sync to mains |
| Other Output Voltages | 110 V 125 V |
| Topology | Line Interactive |
| Waveform Type | Sine wave |
| Nb of power socket outlets | 8 NEMA 5-15R |
| Curve equation | Efficiency |
| Curve fixed loss | 0.0036 |
| Curve load maximum | 100 % |
| Curve load minimum | 1 % |
| Curve proportional loss | 0 |
| Curve square loss | 0.0073 |
| Curve X-axis maximum | 100 % |
| Curve test cond ID | Curve fit of data measured in accordance with the US DOE Test Procedure for Uninterruptible Power Supplies. All measurements taken in normal mode(s), at typical environmental conditions, with 120V/60Hz electrical input and balanced resistive load (PF = 1.0) output. |
| Curve X-axis minimum | 0 % |
| Curve X-axis title | Load |
| Curve X-axis units | Percentage |
| Curve Y-axis maximum | 100 % |
| Curve Y-axis minimum | 50 % |
| Curve Y-axis title | Efficiency |
| Curve Y-axis units | Percentage |
| Graph display | 1 |
| Output voltage | 120 V |
| Maximum configurable power in VA | 1440 VA |
| Rated power in VA | 1440 VA |
| Transfer Time | 6ms typical : 10ms maximum |

Conformance

| | |
|-----------------------------|---|
| Product certifications | CULus ENERGY STAR V2.0 (USA) |
| Standards | CSA C22.2 No. 107.1 FCC Part 15 class A ICES-003 UL 1778 |
| Equipment protection policy | Lifetime : \$150000 |

Environmental

| | |
|---------------------------------------|----------------------------------|
| Ambient air temperature for operation | 32...104 °F (0...40 °C) |
| Relative humidity | 0...95 % |
| Operating altitude | 0...10000 ft |
| Ambient air temperature for storage | 5...113 °F (-15...45 °C) |
| Storage altitude | 0...50000 ft (0.00...15240.00 m) |
| Acoustic level | 45 dBA |
| Heat dissipation | 225 Btu/h |
| Show note OP temperature | No |

Batteries & Runtime

| | |
|------------------------------|-------------------|
| Battery type | Lead-Acid battery |
| Included Battery Modules | 0 |
| Battery Slots Empty | 0 |
| Typical recharge time | 3 h |
| RBC Quantity | 1 |
| Liquid Electrolyte Value | 0 |
| Battery curve | Z |
| Battery Charge Power (Watts) | 136 W rated |
| Battery power in VAH | 408 VAh runtime |
| Battery life | 3...5 year(s) |
| Extendable Run Time | 0 |

Communications & Management

| | |
|---------------|---|
| Free slots | 1 |
| Control panel | Multi-function LCD status and control console |
| Audible Alarm | Alarm when on battery : distinctive low battery alarm : configurable delays |

Surge Protection and Filtering

| | |
|---------------------|--|
| Surge energy rating | 680 J |
| Filtering | Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m |

Ordering and shipping details

| | |
|---------------------|-----------------------------|
| Category | 11309 - APC RESALE PRODUCTS |
| GTIN | 00731304322795 |
| Package weight(Lbs) | 1 lb(US) (0.45 kg) |
| Returnability | No |

Offer Sustainability

| | |
|-----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| Optimized Energy Efficiency | Energy efficient product |

Contractual warranty

| | |
|----------|---|
| Warranty | 3 years repair or replace (excluding battery) and 2 years for battery |
|----------|---|
