


EZ-ARRAY RS-485 to USB Adapter Cable



Datasheet



- Connects a Windows PC USB port to an A-GAGE EZ-ARRAY Series Sensor
- Supports baud rates of 9600, 19200, and 38400
- Converts USB to RS-485 (2-wire) with a Euro-style connector
- Supports Windows XP, Vista, and 7
- Includes cable, User Configuration Tool software, USB driver, and documentation on CD



WARNING:

- **Do not use this device for personnel protection**
- Using this device for personnel protection could result in serious injury or death.
- This device does not include the self-checking redundant circuitry necessary to allow its use in personnel safety applications. A device failure or malfunction can cause either an energized (on) or de-energized (off) output condition.

Models

Model	Adapter	Length
EZA-USB485-01	485 to USB	2 meter

Wiring Diagrams

4-pin M12/Euro-style Male Connector			
	1	Brown	N.C.
	2	White	RS485/D1/B/+
	3	Blue	dc common (GND)
	4	Black	RS485/D0/A/-

Specifications

Input Power

5V dc from USB port

Current

Less than 400 mA at the PC

Operating Conditions

-40 °C to +80 °C (-40 °F to +176 °F)
95% at +50 °C maximum relative humidity (non-condensing)

USB Connector

USB type A plug

USB Standard

2.0

RS-485

2-wire; 9.6k, 19.2k, or 38.4k; 8 data bits; 1 stop bit; no parity

RS-485 Connector

Euro-style connector


Length

2 meters



Dimensions

All measurements are listed in millimeters, unless noted otherwise.



Banner Engineering Corp. Limited Warranty

Banner Engineering Corp. warrants its products to be free from defects in material and workmanship for one year following the date of shipment. Banner Engineering Corp. will repair or replace, free of charge, any product of its manufacture which, at the time it is returned to the factory, is found to have been defective during the warranty period. This warranty does not cover damage or liability for misuse, abuse, or the improper application or installation of the Banner product.

THIS LIMITED WARRANTY IS EXCLUSIVE AND IN LIEU OF ALL OTHER WARRANTIES WHETHER EXPRESS OR IMPLIED (INCLUDING, WITHOUT LIMITATION, ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE), AND WHETHER ARISING UNDER COURSE OF PERFORMANCE, COURSE OF DEALING OR TRADE USAGE.

This Warranty is exclusive and limited to repair or, at the discretion of Banner Engineering Corp., replacement. **IN NO EVENT SHALL BANNER ENGINEERING CORP. BE LIABLE TO BUYER OR ANY OTHER PERSON OR ENTITY FOR ANY EXTRA COSTS, EXPENSES, LOSSES, LOSS OF PROFITS, OR ANY INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES RESULTING FROM ANY PRODUCT DEFECT OR FROM THE USE OR INABILITY TO USE THE PRODUCT, WHETHER ARISING IN CONTRACT OR WARRANTY, STATUTE, TORT, STRICT LIABILITY, NEGLIGENCE, OR OTHERWISE.**

Banner Engineering Corp. reserves the right to change, modify or improve the design of the product without assuming any obligations or liabilities relating to any product previously manufactured by Banner Engineering Corp. Any misuse, abuse, or improper application or installation of this product or use of the product for personal protection applications when the product is identified as not intended for such purposes will void the product warranty. Any modifications to this product without prior express approval by Banner Engineering Corp will void the product warranties. All specifications published in this document are subject to change; Banner reserves the right to modify product specifications or update documentation at any time. Specifications and product information in English supersede that which is provided in any other language. For the most recent version of any documentation, refer to:

www.bannerengineering.com.

For patent information, see www.bannerengineering.com/patents.