





FEATURES

- Super industrial strength removes tough stains and soils
- Does not contain butyl, chlorinated or petroleum solvents, bleach, ammonia, or abrasives
- Alkaline formula inhibits flash rusting
- Rinses clean
- Safe of most surfaces (not for use with Magnesium & Aluminum).
- VOC compliant in all 50 states
- Nonfood Compounds Program Listed Category Code: C1 Registration #059854

APPLICATIONS

- Bilges
- Carbon blocks
- Grease traps
- Exhaust hoods
- Compressors
- Concrete
- Engines
- Tanks

- Hoists • Tools
- Machinery
- Garage floors
- Drill presses
- Sidewalks
- Driveways
- Ovens

IS (IDENTIFICATION SYSTEM) BIO

SPECIFICATIONS AND APPROVALS

- Tampa Electric Co.
- Halliburton
- Kimberly-Clark
- Inland Steel
- Timken Steel
- Universal-Leaf
- PPG Glass Mfg.
- NSF

- Honda Corp.
 - General Motors Co.
 - Ford Motor Co.
 - Kodak
 - Hazelton Pump
- Dresser Rand
- Caterpillar

AVAILABLE PRODUCTS

Part No.		Net Contents	Contoinor	Casa Daak	
US	Canada	Net Contents	Container	Case Pack	Case Wt.
02728	C02728	28 fl.oz. (828 mL)	Trigger	12	27.0
02720	C02720	18 wt.oz./510 g/525 mL	Aerosol	12	18.0
02701	C02701	1 gal. (3.78 L)-concentrate	Bottle	4	38.0
02705	C02705	5 gal. (18.93 L)-concentrate	Pail	1	46.0
02755	C02755	55 gal. (208 L)-concentrate	Drum	1	535.0
02765	C02765	55 gal. (208 L)	Drum	1	535.0



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY! 800.241.8334 | www.lpslabs.com

©2019 ITW Pro Brands • LPS® is a registered trademark of Illinois Tool Works All Rights Reserved • TDS02720 • 190604

S Precision Clean Multi-Purpose Cleaner/Degreaser

PROPERTIES	AEROSOL	CONCENTRATE	RTU	
Appearance/physical state	Gas/Aerosol	Clear/Liquid	Clear/Liquid	
Odor	Citrus	Citrus	Mild/Citrus	
Melting point/freezing point	Not available	Not available	Not available	
Boiling point/range	212°F (100°C)	212°F (100°C)	212°F (100°C)	
Vapor pressure	< 17.5 mm Hg @20°C	< 17.5 mm Hg @20°C	< 17.5 mm Hg @20°C	
Partition coefficient	Not available	Not available	Not available	
Percent volatile	97%	>90%	96%	
рН	12.9	13	12.5	
Propellant	Petroleum Gases, Liquified	Not applicable	Not applicable	
VOC Content	5.8 % per U.S. State and Federal Consumer Product Regulations	1.5 % per U.S. State and Federal Con- sumer Product Regulations	0.38% per U.S. State and Federal Consumer Product Regulations	
Color	Greenish-blue	Greenish-blue	Green	
Flash point	Not established	Not established	Not established	
Density	Not available	8.87 lb/gal	8.44 lb/gal	
Evaporation rate	1 BuAc	1 BuAc	1 BuAc	
Vapor density	>1	>1	>1	
Auto-ignition temperature	Not available	Not available	Not available	
Viscosity < 3 cSt Not available		Not available	Low viscosity comparable to water (water = 1 cST. @ 20°C)	
Specific Gravity (water=1)	1 - 1.03 @ 20°C	1.06 @ 20°C	1.01 @ 20°C	
Temperature Range °F(°C)	Not available	Not available	Not available	
4-Ball Weld Load	Not applicable	Not applicable	Not applicable	
Soplubility in Water	100%	100%	100%	

DIRECTIONS

(Aerosol) Shake well before using. Spray directly on surface to be cleaned. Allow foam to set 10 to 30 seconds. Wipe of rinse clean. Conductive (water-based). Do not use on energized equipment. If equipment is still dirty or greasy, repeat procedure. (Bulk) KEEP FROM FREEZING. MIX WELL BEFORE USING. Rinse and/or wipe dry any residue. Test for compatibility on delicate materials.

Dilution Ratio Product:				
Water	Equipment	Applications		
1:4	Parts Washers	Carbon blocks, engines, exhaust hoods, forklifts, graffiti, marine, tanks, varnish		
1:5	Dip Tanks	Aviation, compressors, food processing equipment, floors, hoists, lifts, printing presses, tools		
1:7	Tumblers	Drill presses, oily parts, pulleys and wires		
1 : 10	Ultrasonic	Cleaning electrical parts (Deionized water rinse/dry)		
1:4-20	Steam Cleaner	Engines, parts		
1:60	Trigger Sprayer	Floors, leather and fabrics, tile, walls, wood		
1:40-80	Pressure Washer	Cleaning parts, floors, trucks, etc.		
1 : 100	Trigger Sprayer	Appliances, formica, general cleaning of glass, walls		

STORAGE

Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS)

DISPOSAL INFORMATION

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose in accordance with all applicable regulations.



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY! 800.241.8334 | www.lpslabs.com

2019 ITW Pro Brands • LPS® is a registered trademark of Illinois Tool Works All Rights Reserved • TDS02720 • 190604