



ChainMate

Chain & Wire Rope Lubricant



FEATURES

- Fortified with molybdenum disulfide
- Increases chain and wire rope life
- Effective under extreme pressure and temperature ranges
- Contains water displacing solvents to quickly penetrate into cracks and core of wire rope
- Anti-sling adhesion
- Reduces wear caused by friction and corrosion
- Provides maximum lubrication and corrosion protection
- VOC compliant in all 50 state

APPLICATIONS

- Bushings
- Cables
- Chains
- Cranes
- Cutting tools
- Drag lines
- Drives
- Forklifts
- Pins
- Pulleys
- Rollers
- Saws
- Sprockets
- Wire ropes

SPECIFICATIONS AND APPROVALS

- CARB Compliant
- Ford Motor Co.
- General Motors Co.
- Honda Corp.
- Kimberly-Clark
- Minntac - US Steel
- OTC Compliant
- PPG Glass Mfg.
- Pratt & Whitney Canada MMC 21539
- Whirlpool

PROPERTIES

Appearance/physical state	Aerosol: Gas
Odor	Slight petroleum odor.
Melting point/freezing point	Not established
Boiling point/range	Not established
Vapor pressure	35 psi @ 75°F
Partition coefficient	Not established
Percent volatile	17%
Flammability limit	Flammable gas.
Propellant	Petroleum Gases
VOC Content	22.33% per US State and Federal Consumer Product Regulations
Color	Dark grey, Black
Flash point	< -4.0°F (< -20.0°C) Tag Closed Cup
Relative density	Not available.
Evaporation rate	Not established
Vapor density	> 1
Auto-ignition temperature	Not established
Viscosity	150 cP @ 75°F / 23.9°C
Specific Gravity (water=1)	0.88 @ 20°C
Temperature Range °F(°C)	Not established
4-Ball Weld Load	Not established

DIRECTIONS

For best results, clean chain or wire rope before applying. Shake well before using, until ball moves freely. Hold can upright and spray from 10-12 inches away. Use attached extension tube for pinpoint application. Apply a light coating. Reapply as needed.

HANDLING

Pressurized container: Do not pierce or burn, even after use. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

STORAGE

Keep container in a cool, well-ventilated area. Avoid all sources of ignition (spark or flame). Store between 40°F (5°C) and 120°F (49°C). Store aerosols as Level 3 Aerosol (NFPA 30B). Store all materials in a dry, well ventilated area. Avoid breathing vapors

DISPOSAL INFORMATION

Waste must be disposed of in accordance with any and all applicable environmental control rules and/ or regulations.

AVAILABLE PRODUCTS

Part No.		Net Contents	Container Type	Units/Case	Case Weight
US	Canada				
02416	C02416	11 wt oz / 312 g / 405 mL	aerosol	12	12 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved