



BFX

All-Purpose Cleaner



FEATURES

- Industrial strength for hard to remove soils and oils
- Water-based and biodegradable for safer cleaning alternative
- Ideal for parts washers and pressure washers
- Safe to use on most surfaces except for magnesium
- Non-corrosive formula to inhibit flash rusting
- Does not contain butyl or phosphates

APPLICATIONS

- Aluminum
- Carbon
- Carpet
- Chrome
- Counters
- Diesel Fuel
- Dip Tanks
- Floor Scrubbers
- Machinery
- Painted Surfaces
- Parts Washers
- Pressure Sprayers
- Smoke
- Soot
- Spot Cleaning
- Vents

SPECIFICATIONS AND APPROVALS

- NSF International, C1

PROPERTIES

Appearance / Physical State	Liquid
Odor	Sassafras
Melting / Freezing Point	32°F (0°C)
Boiling Point / Range	212°F (100°C)
Vapor Pressure	17.5 mm Hg @ 20°C
Partition Coefficient	Not available
Percent volatile	99%
Flammability	Not available
Propellant	Not available
VOC Content	0% per US State & Federal Consumer Product Regulations
Color	Light yellow
Flash Point	None
Density	Not available
Evaporation Rate	1 BuAc
Vapor density	>1
Auto-Ignition Temperature	Not available
Viscosity	1 cST@ 20°C
Specific Gravity	1.02
Temperature Range	Not available
4-Ball Weld Load	Not applicable

DIRECTIONS

(Trigger) Turn nozzle to spray or stream position. Pull trigger to spray. (Bulk) KEEP FROM FREEZING. MIX WELL BEFORE USING. Rinse and/or wipe dry any residue. Test for compatibility on delicate materials.

Dilution Ratio Product:

Water Equipment Applications

1: 4 Parts Washers Carbon blocks, engines, exhaust hoods, forklifts, graffiti, marine, tanks, varnish

1: 5 Dip Tanks Aviation, compressors, food processing equipment, floors, hoists, lifts, printing presses, tools

1: 7 Tumblers Drill presses, oily parts, pulleys and wires

1: 10 Ultrasonic Cleaning electrical parts (Deionized water rinse/dry)

1: 4-20 Steam Cleaner Engines, parts

1: 60 Trigger Sprayer Floors, leather and fabrics, tile, walls, wood

1: 40-80 Pressure Washer Cleaning parts, floors, trucks, etc.

1: 100 Trigger Sprayer Appliances, formica, general cleaning of glass, walls

HANDLING

Avoid prolonged exposure. Observe good industrial hygiene practices.

STORAGE

Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS)

DISPOSAL

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose in accordance with all applicable regulations.

AVAILABLE PRODUCTS

US	Part No.		Net Contents	Container Type	Units/Case	Case Weight
	Canada					
05528		C05528	28 fl oz / 828 mL	trigger	12	27 lbs
05501			1 gal / 3.78 L	bottle	4	37 lbs
05555			55 gal / 208 L	drum	1	535 lbs



CONTACT YOUR ITW PRO BRANDS REPRESENTATIVE TODAY!

800.241.8334 | www.itwprobrands.com

LPS®, SCRUBS®, DYKEM®, Accu-Lube®, DYMON®, Spray Nine®, and Cedar® are registered trademarks and Rustlick™, Diamondkote™, and MetalMates™ are trademarks of Illinois Tool Works • All Rights Reserved