

# BRITE-MARK® Roughneck

# Permanent Paint Marker/Valve Action

#### **DIRECTIONS**

- · Shake well with cap on
- Depress tip to start flow
- Replace cap when not in use

#### **FEATURES**

- BRITE-MARK<sup>®</sup> Roughneck is a general purpose paint marker that writes on almost any surface.
- BRITE-MARK<sup>®</sup> is available in 3 marker styles BRITE-MARK<sup>®</sup> Medium, BRITE-MARK<sup>®</sup> Roughneck, BRITE-MARK<sup>®</sup> Threaded Cap
- Makes permanent bright marks on metal, rubber, plastic, glass, concrete, leather, stone, wood, vinyl and more.
- Quick drying, oil based, UV resistant paint withstands harsh indoor and outdoor conditions.
- Does not contain any HAP's (Hazardous Air Pollutants) which makes them a smart alternative to using spray paint and stencil for big, bold marks.
- Does not contain any reportable amounts of Xylene.
- Markers can be used to permanently identify inventory, assemblies, tools, finished products or work in progress while resisting most work related abuses or compounds.
- Valve action mechanism prevents paint in barrel from drying when the cap is left off.
- Bullet tips are replaceable to assure complete use of paint in each marker.
- BRITE-MARK<sup>®</sup> Roughneck markers have a heavy duty aluminum body with large paint capacity.
- BRITE-MARK<sup>®</sup> Roughneck has a tough polyester tip designed to write through grease, dirt, water and oil.

#### MATERIALS COMPATIBILITY

- Safe on most surfaces.
- Removable with DYKEM® Remover & Cleaner.
- Surface tests should be run to determine compatibility prior to use.

## **HEALTH AND SAFETY**

- Flammable liquid and vapor. Keep away from heat, sparks and flame. Use only with adequate ventilation. Avoid contact with skin and eyes.
- Refer to SDS (Safety Data Sheet) for complete information on health and safety. Visit our website at www.dykem.com to obtain an MSDS.



#### PHYSICAL PROPERTIES

| Appearance / Physical State | Varies  |  |
|-----------------------------|---|--|
| Odor                        | Sweet   |  |
| VOC Content                 | 45% - 77% by weight   |  |
| Flash Point                 | 81°F  |  |
| Dry Time                    | 25-35 seconds *Note: Drying time may vary depending on film |  |

## **AVAILABLE IN**

| Color  | Marker Tip         | Part # |
|--------|--------------------|--------|
| black  | medium, felt (#16) | 84202  |
| blue   | medium, felt (#16) | 84201  |
| green  | medium, felt (#16) | 84207  |
| red    | medium, felt (#16) | 84206  |
| orange | medium, felt (#16) | 84205  |
| white  | medium, felt (#16) | 84203  |
| yellow | medium, felt (#16) | 84204  |

