

Selectorswitch, metal Maintained, short lever left, 1NO right position, A Cam 2 position Complete device white insert Non-Illuminated UL file E22655 in Vol. 6 (7) Sec. 13 (2)

Enclosure

number of command points	1
delivery state	
<ul style="list-style-type: none"> as a kit 	No

Actuator

material of the actuating element	plastic
number of contact modules	1
type of unlocking device	rotate-to-unlatch mechanism
number of switching positions	2

Front ring

product component front ring	Yes
design of the front ring	standard
material of the front ring	metal

General technical data

product function	
<ul style="list-style-type: none"> positive opening 	No
product component	
<ul style="list-style-type: none"> light source 	No
insulation voltage	
<ul style="list-style-type: none"> rated value 	600 V
protection class IP	IP66
<ul style="list-style-type: none"> of the terminal 	IP20
operating frequency maximum	600 1/h
thermal current	10 A

Auxiliary circuit

number of NC contacts for auxiliary contacts	0
number of NO contacts for auxiliary contacts	1
<ul style="list-style-type: none"> operating current at AC-15 at 110 V rated value 	60 A
<ul style="list-style-type: none"> operational current at AC-15 at 230 V rated value 	30 A
<ul style="list-style-type: none"> operating current at AC-15 at 400 V rated value 	15 A
<ul style="list-style-type: none"> operating current at AC-15 at 500 V rated value 	12 A

Connections/ Terminals

type of electrical connection	screw-type terminals
tightening torque of the screws in the bracket	20 N·m
tightening torque [lbf·in]	
• with screw-type terminals	8 lbf·in

Installation/ mounting/ dimensions

shape of the installation opening	round
--	-------

Certificates/ approvals

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52SA2AABK0>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52SA2AABK0>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/US2:52SA2AABK0>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52SA2AABK0&lang=en

last modified:

10/09/2020