

Keyed selector switch, metal Maintained A Cam 2 position Operator only Non-Illuminated Key type 501CH (standard) Key removable in all positions UL file E22655 in Vol. 6 (7) Sec. 13 (2)



Figure similar

design of the product	Actuator round
Enclosure	
number of command points	1
delivery state	No
• as a kit	
Actuator	
design of the operating mechanism	Key-operated switch
material of the actuating element	metal
type of unlocking device	key unlatching
number of switching positions	2
switch position for key distraction	removable in every position
lock make	ILLINOIS
key number	501CH
Front ring	
product component front ring	Yes
design of the front ring	standard
material of the front ring	metal

color of the front ring	chrome
-------------------------	--------

Holder

material of the holder	Metal
------------------------	-------

General technical data

product component	
• light source	No
degree of pollution	1
protection class IP	IP66
operating frequency maximum	600 1/h

Installation/ mounting/ dimensions

shape of the installation opening	round
-----------------------------------	-------

Certificates/ approvals

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52SC6AE>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52SC6AE>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/US2:52SC6AE>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52SC6AE&lang=en

last modified:

10/09/2020