## **SIEMENS**

Data sheet	US2:52SA2BCE
	Selector swich, metal Spring return from right Short lever position, B Cam 3 position Operator only white insert Non-Illuminated UL file E22655 in Vol. 6 (7) Sec. 13 (2)
design of the product	Actuator round
Enclosure	
number of command points	1
delivery state	
● as a kit	No
Actuator	
design of the operating mechanism	selector switch
material of the actuating element	plastic
type of unlocking device	rotate-to-unlatch mechanism
number of switching positions	3
Front ring	
product component front ring	Yes
design of the front ring	standard
material of the front ring	metal
color of the front ring	chrome
Holder	
material of the holder	Metal
General technical data	
product component	
• light source	No
degree of pollution	1
protection class IP	IP66
operating frequency maximum	600 1/h
nstallation/ mounting/ dimensions	
shape of the installation opening	round
Certificates/ approvals	
Further information	
Information, and Downloadcenter (Catalogs	Prochures \

Information- and Downloadcenter (Catalogs, Brochures,...) https://www.siemens.com/ic10

Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52SA2BCB

Cax online generator http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52SA2BCB

Service&Support (Manuals, Certificates, Characteristics, FAQs,...) https://support.industry.siemens.com/cs/ww/en/ps/US2:52SA2BCB

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) <a href="http://www.automation.siemens.com/bilddb/cax\_de.aspx?mlfb=US2:52SA2BCB&lang=en">http://www.automation.siemens.com/bilddb/cax\_de.aspx?mlfb=US2:52SA2BCB&lang=en</a>

10/09/2020 last modified: