



Creating Safe Work Solutions During COVID-19

MQEAC-606RA

► SINGLE-ENDED CORDSETS



Mirco-style 12 mm Dual Key

6-pin Female Right-angle

Standard Colors, RD/WH, RD,GN, RD/YW, RD/BK

2 m (6 ft) Length

Nickle Plated Brass Coupling Nut PUR-Black

Part Number: 77322

SPECIFICATIONS

Number of Contacts	6
Number of Connectors	1
Cable Jacket Material	PVC
Cable Jacket Color	Yellow
Connector Body Material/Color	PUR Black
Outside Cable Diameter (mm)	5.6
Cordset Length (m)	1.83
Trunk Length (m)	No Trunk
Shield/No Shield	No Shield
Coupling Material/Color	Nickel Plated Brass
Maximum Temp. (°C)	105
Current Rating (A)	4.0



Contact Us

Minimum Temp. (°C)	-40
Voltage Rating (V)	250 V ac/dc
IP Rating	IP67
Primary Connector Type	MICRO
Primary Coupling Method	M12 Dual Key
Primary Gender	Female
Primary Orientation	Right Angle
Primary Number of Conductors	6
Primary AWG	22
Secondary Connector Type	Flying Leads
Feature: Hazardous Area	No
Oil/Grease Resistant	No



Banner Engineering Corp. | 9714 Tenth Avenue North | Minneapolis, MN 55441 | United States of America



Contact Us