



Overview

Presentation	Features integrated camera and sensors (temperature, humidity, airflow, dewpoint, camera motion). Supports 3 additional external cameras pods, 2 sensor pods and up to 16 Universal Sensors.
Lead time	Usually in Stock

General

Provided equipment	Installation guide USB cable Wall Mounting Brackets
Number of Universal Sensor Ports	3
Number of Sensor Pods Supported	2
Number of Universal Sensors Supported	16
Number of Cameras Supported	4

Physical

Maximum Depth	7.76 in (19.7 cm)
Maximum Height	9.53 in (24.2 cm)
Net Weight	1.81 lb(US) (0.82 kg)
Maximum Width	9.06 in (23 cm)

Environmental

Ambient air temperature for operation	32...113 °F (0...45 °C)
Operating altitude	0...10000 ft
Relative humidity	0...95 %
Ambient air temperature for storage	5...149 °F (-15...65 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)

Communications & Management

Communication network type	RJ-45 10/100 Base-T
Communication port protocol	DHCP DNS HTTP HTTPS SMTP SNMP v3 SOCKS TCP/IP

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Ordering and shipping details

GTIN	00731304339137
Package weight(Lbs)	5.58 lb(US) (2.53 kg)

Packing Units

Package 1 Height	14.96 in (38 cm)
Package 1 width	16.77 in (42.6 cm)
Package 1 Length	14.13 in (35.9 cm)

Offer Sustainability

EU RoHS Directive	Under investigation
-------------------	---------------------

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------