



Overview

Presentation	Supports up to 4 external camera pods, 12 sensor pods and up to 78 Universal Sensors.
Lead time	Usually in Stock



General

Provided equipment	Country-specific detachable power cord Documentation CD Installation guide Rack Mounting brackets Temperature/Humidity Sensor USB cable
Camera Frame Rate	Up to 30fps
Product compatibility	4 - 20mA Sensor Camera Pod 120 CCTV Adapter Pod 120 Rack Sensor Pod 150 Room Sensor Pod 155 Sensor Pod 120 Pelco IPSD4N-W0 Analog CCTV cameras via USB CCTV Adapter Pod NetBotz USB Camera Pod NTSC camera PAL camera Pelco IP110-CHV9 Pelco IP3701H-2
Display resolution	Up to 1280x1024
External Sensor Connection Type	4-20mA Sensor Inputs 4 Alarm Beacon 1 Fluid Rope Leak Sensor 1 Relay Outputs 2
APC Universal Sensors Supported	0-5V Door contact Dry Contact Humidity Smoke Fluid Spot Leak Temperature Vibration
Number of Universal Sensor Ports	6
Number of Sensor Pods Supported	12
Number of Universal Sensors Supported	72
Number of Cameras Supported	4 Networked 4 USB

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Physical

Maximum Depth	3.66 in (9.3 cm)
Maximum Height	1.69 in (4.3 cm)
Mounting location	Front
Net Weight	3.84 lb(US) (1.74 kg)
Maximum Width	17.01 in (43.2 cm)

## Conformance

Standards	FCC Part 15 class A ICES-003
Product certifications	AS/NZS 3548 (C-Tick) Class A CUL Listed CE GOST IRAM Low Voltage Directive 2006/95/EC NOM UL Listed VCCI Class A VDE

## Environmental

Ambient air temperature for operation	32...113 °F (0...45 °C)
Operating altitude	0...10000 ft
Relative humidity	0...95 %
Ambient air temperature for storage	5...149 °F (-15...65 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)

## Communications & Management

Communication network type	RJ-45 10/100 Base-T
Communication port protocol	DHCP DNS HTTP HTTPS SMTP SOCKS TCP/IP



## Ordering and shipping details

GTIN	00731304284949
Package weight(Lbs)	6.31 lb(US) (2.86 kg)

## Packing Units

Package 1 Height	4.49 in (11.4 cm)
Package 1 width	21.50 in (54.6 cm)
Package 1 Length	9.02 in (22.9 cm)

## Offer Sustainability

EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	 Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------