# P11GTV

APC Power-Saving Performance SurgeArrest, 11 Outlets with Phone and Video Protection, 120V



#### Overview

Lead time	Usually in Stock	



#### General

Provided equipment	Coaxial cable Telephone Cable User Manual

### Physical

Cable length	6 ft (1.83 m)	
Color	Black	
Maximum Depth	14.30 in (36.32 cm)	
Maximum Height	1.57 in (4 cm)	
Net Weight	2.45 lb(US) (1.11 kg)	
Maximum Width	4.70 in (11.939 cm)	

#### Input

Input Frequency	50/60 Hz +/- 5 Hz manual switch
Plug standard	NEMA 5-15P
Switching current capacity	15 A
Nominal Input Voltage	120 V

#### Output

Number of power socket outlets	11	
Outlet standard	NEMA 5-15R	

#### Conformance

Product certifications	ETL	
Standards	UL 1363 UL 1449	
Equipment protection policy	Lifetime : \$300000	

#### Environmental

Ambient air temperature for operation	32104 °F (040 °C)
Relative humidity	095 %
Operating altitude	015000 ft
Ambient air temperature for storage	5113 °F (-1545 °C)
Storage altitude	050000 ft (0.0015240.00 m)

# Surge Protection and Filtering

NM Surge Response Time (ns)	1 ns common mode
EMI/RFI Noise rejection (100 kHz to 10 MHz)	70 dB
Surge energy rating	3400 J
Data Line Protection	Analog phone line for phone/fax/modem/DSL (RJ11 connector) Coaxial cable for CATV/SATV/modem/Audio-Video (coax connector)

# Ordering and shipping details

GTIN	00731304269236
Package weight(Lbs)	2.89 lb(US) (1.31 kg)

#### **Packing Units**

1 doking office	
Package 1 Height	2.31 in (5.87 cm)
Package 1 width	9.92 in (25.2 cm)
Package 1 Length	16.85 in (42.8 cm)
SCC14	10731304269233
Number of Units in Package 2	6
Package 2 Weight	20.35 lb(US) (9.23 kg)
Package 2 Height	18 in (457.20 mm)
Package 2 width	11 in (279.40 mm)
Package 2 Length	16 in (406.40 mm)
Number of Units in Package 3	192

#### Offer Sustainability

EU RoHS Directive	Compliant  EVEU RoHS Declaration

### Contractual warranty

Warranty	Lifetime