



PMIopen - Operator panel with 5.7" touchscreen, open HMI platform for every common visualisations software, configurable with PMI Assistant.

Technical details

Certifications:	CE;cULus Listed;EAC (Eurasian)
Resolution:	320 x 240
Display type:	TFT
Display diagonal:	5.7 Zoll
Colour depth:	65536
Touchscreen:	Resistive
Possible PMI applications:	PSS/PSSu/PNOZmulti;PNOZmulti diagnostics;Diagnostics PSS / SafetyBUSp
Number of Ethernet interfaces:	1
Number of RS 232 interfaces:	1
Supply voltage (V):	24,0
Supply voltage type:	DC
Operating system:	Windows Embedded CE 6.0
Width dimension:	170.0 mm
Height dimension:	144.0 mm
Depth dimension:	40.0 mm
Gross weight:	1141 g
Net weight:	659 g
Ambient temperature:	0 - 50 °C

Optional accessories

	261905	RT-Licence PVIS OPC-Srv f.PMI, PtoP
	261906	RT-Licence PVIS OPC-Srv f.PMI, 8 devices
	269700	power connector PMI (3 pcs)
	269701	seal for PMIvisu, PMlopen, PMImicro
	310300	Serial programming cable
	313100	SD Memory Card 512MB
	265010	Zenon Operator Dev 1024
	265210	Zenon Operator RT PMI
	265220	Zenon Operator 7.20 RT PMI



THE SPIRIT OF SAFETY

265020

Zenon Operator 7.20 Dev 1024
