# Product data sheet Characteristics

# 9007MS05S0410

9007MS limit switch - cat whisker any direction spring rtn. - 12' bottom cable



| Main                      |                        |
|---------------------------|------------------------|
| Range of product          | 9007                   |
| Series name               | Miniature potted       |
| Product or component type | Limit switch           |
| Device short name         | 9007MS/ML              |
| Sensor design             | Miniature              |
| Body type                 | Fixed                  |
| Head type                 | Multi-directional head |
| Material                  | Metal                  |
| Body material             | Cast zinc              |
| Number of poles           | 1                      |

#### Complementary

| Fixing mode   | By the body   |
|---|---|
| Movement of operating head  | Multi-directional   |
| Type of operator  | Spring return wire whisker steel -  |
| Type of approach  | Multi-directional approach  |
| Switch actuation  | By any moving part  |
| Contacts type and composition   | NC-NO   |
| Switch function   | SPDT  |
| Contact form  | Form C  |
| Contacts material   | Silver contacts   |
| Contact operation   | Snap action   |
| Positive opening  | Without   |
| Electrical connection   | Pre-wired cable bottom  |
| Type of cable   | SJTO AWG 18), 12 ft (3.66 m), Gray  |
| Terminals description ISO n°1   | (Green-yellow)Gnd<br>(Red)NC<br>(Black)Com<br>(white)NO   |
| Maximum force for tripping  | 15 ozf  |
| [le] rated operational current  | 6 A 120 V AC, A300 NEMA rating designation  |
| [.a] .aca applicational outroit   | 3 A 240 V AC, A300 NEMA rating designation<br>5 A 28 V DC   |
| [Ithe] conventional enclosed thermal current  | 3 A 240 V AC, A300 NEMA rating designation  |
|   | 3 A 240 V AC, A300 NEMA rating designation<br>5 A 28 V DC   |
| [Ithe] conventional enclosed thermal current  | 3 A 240 V AC, A300 NEMA rating designation<br>5 A 28 V DC<br>10 A<br>300 V 3)UL 508   |
| [Ithe] conventional enclosed thermal current [Ui] rated insulation voltage  | 3 A 240 V AC, A300 NEMA rating designation<br>5 A 28 V DC<br>10 A<br>300 V 3)UL 508<br>300 V 3)CSA C22.2 No 14  |
| [Ithe] conventional enclosed thermal current [Ui] rated insulation voltage  Electrical durability   | 3 A 240 V AC, A300 NEMA rating designation<br>5 A 28 V DC<br>10 A<br>300 V 3)UL 508<br>300 V 3)CSA C22.2 No 14<br>100000 cycles                       |
| [Ithe] conventional enclosed thermal current [Ui] rated insulation voltage  Electrical durability  Mechanical durability  | 3 A 240 V AC, A300 NEMA rating designation 5 A 28 V DC  10 A  300 V 3)UL 508 300 V 3)CSA C22.2 No 14  100000 cycles  CE UL                            |
| [Ithe] conventional enclosed thermal current [Ui] rated insulation voltage  Electrical durability  Mechanical durability  Marking   | 3 A 240 V AC, A300 NEMA rating designation 5 A 28 V DC  10 A  300 V 3)UL 508 300 V 3)CSA C22.2 No 14  100000 cycles  CE UL CSA                        |
| [Ithe] conventional enclosed thermal current  [Ui] rated insulation voltage  Electrical durability  Mechanical durability  Marking  Sale per indivisible quantity         | 3 A 240 V AC, A300 NEMA rating designation 5 A 28 V DC  10 A  300 V 3)UL 508 300 V 3)CSA C22.2 No 14  100000 cycles  CE UL CSA                        |
| [Ithe] conventional enclosed thermal current  [Ui] rated insulation voltage  Electrical durability  Mechanical durability  Marking  Sale per indivisible quantity  Height | 3 A 240 V AC, A300 NEMA rating designation 5 A 28 V DC  10 A  300 V 3)UL 508 300 V 3)CSA C22.2 No 14  100000 cycles  CE UL CSA  1  1.75 in (44.45 mm) |

#### Environment

| Shock resistance                      | 35 gn 9 ms IEC 60068-2-27  |
|---------------------------------------|--|
| Vibration resistance                  | 10 gn 751200 Hz)IEC 60529  |
| NEMA degree of protection             | NEMA 1 Nema type 250<br>NEMA 12 Nema type 250<br>NEMA 13 Nema type 250 |
| IP degree of protection               | IP54 IEC 60529   |
| Ambient air temperature for operation | -40220 °F (-40104 °C)  |
| Ambient air temperature for storage   | -40220 °F (-40104 °C)  |
| Protective treatment                  | Epoxy powder coat  |
| Product certifications                | UL<br>CSA<br>CE  |
| Standards                             | E78403<br>LR 25490 Class 32 11 03                                      |

#### Ordering and shipping details

| a complete and a comp |                                     |
|--|-------------------------------------|
| Category   | 22431 - LIMIT SWITCHES, TYPE 9007MS |
| Discount Schedule  | DS1                                 |
| GTIN   | 00785901159049                      |
| Nbr. of units in pkg.  | 1                                   |
| Package weight(Lbs)  | 1.2 lb(US) (0.54 kg)                |
| Returnability  | No                                  |
| Country of origin  | MX                                  |
|  |                                     |

### Packing Units

| Package 1 Height | 30.48 in (77.419 cm)  |
|------------------|-----------------------|
| Package 1 width  | 12.00 in (30.480 cm)  |
| Package 1 Length | 77.42 in (196.645 cm) |

## Offer Sustainability

| California proposition 65 | WARNING: This product can expose you to chemicals including: Di-isodecyl phthalate (DIDP) and Diisononyl phthalate (DINP) which is known to the State of California to cause Carcinogen and Reproductive harm. For more information go to www.p65warnings.ca.gov |
|---------------------------|--|
| EU RoHS Directive         | Not applicable, out of EU RoHS legal scope   |
| Environmental Disclosure  | Product Environmental Profile  |

#### Contractual warranty

| Warranty | 18 months |
|----------|-----------|
|----------|-----------|