



### Main

Product or component type	Industrial Control Transformer
Power Rating	150 VA
Primary Voltage	230/460/575 V
Secondary Voltage	95/115 V
Type	T

### Complementary

Number of Phases	1 phase
Power Rating	150 VA
Primary to Secondary Voltage	230/460/575 V 95/115 V
Temperature rise	55 °C
Electrical connection	Screw clamp terminals
Maximum Height	3.2 in (81.28 mm)
Maximum Width	3.75 in (95.25 mm)
Maximum Depth	3.59 in (91.19 mm)
Material	Copper winding
Fingersafe Cover Compatibility	FSC1

### Environment

Product certifications	UL listed file E61239 CSA file LR37055 guide 184-N-90
Enclosure Type	Not rated (open device)
Insulation temperature	221 °F (105 °C)

### Ordering and shipping details

Category	16200 - 9070 T (NOT TF) 50-200VA
Discount Schedule	CP8
GTIN	00785901845621
Nbr. of units in pkg.	1
Package weight(Lbs)	5.1 lb(US) (2.31 kg)
Returnability	Yes
Country of origin	US

### Packing Units

Package 1 Height	5.40 in (13.716 cm)
Package 1 width	7.20 in (18.288 cm)
Package 1 Length	6.20 in (15.748 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
PVC free	Yes

## Contractual warranty

Warranty	10 Years
----------	----------