



Overview

Lead time	Usually in Stock
-----------	------------------

General

Provided equipment	User Manual USB cable
--------------------	--------------------------

Physical

Cable length	6 ft (1.83 m)
Color	Black
Maximum Depth	17.28 in (43.9 cm)
Maximum Height	8.62 in (21.9 cm)
Net Weight	44.31 lb(US) (20.1 kg)
Maximum Width	6.73 in (17.1 cm)

Input

Input Frequency	50/60 Hz +/- 3 Hz auto-sensing
Plug standard	NEMA 5-15P
Efficiency at full load	75...154 V adjustable 82...144 V
Other Input Voltages	110 V 125 V
Nominal Input Voltage	120 V

Output

Kw Rating	700 W
Max Configurable Power (Watts)	700 W
Harmonic distortion	Less than 5%
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz sync to mains
Other Output Voltages	110 V 125 V
Topology	Line Interactive
Waveform Type	Sine wave
Nb of power socket outlets	8 NEMA 5-15R
Output voltage	120 V

Conformance

Product certifications	CULus ENERGY STAR V2.0 (USA)
Standards	CSA C22.2 No. 107.1 FCC Part 15 class A ICES-003 UL 1778
Equipment protection policy	Lifetime : \$150000

Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	5...113 °F (-15...45 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)
Acoustic level	41 dBA
Online Thermal Dissipation	175 Btu/h

Batteries & Runtime

Battery type	Lead-Acid battery
Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	3 h
RBC Quantity	1
Liquid Electrolyte Value	0

Communications & Management

Free slots	1
Control panel	Multi-function LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

Surge Protection and Filtering

Surge energy rating	680 J
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m



Ordering and shipping details

Category	11309 - APC RESALE PRODUCTS
GTIN	00731304322771
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	No

Packing Units

Package 1 Height	12.99 in (33 cm)
Package 1 width	12.99 in (33 cm)
Package 1 Length	23.23 in (59 cm)
Number of Units in Package 3	12

Offer Sustainability

EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
Optimized Energy Efficiency	Energy efficient product

Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery
----------	---