

NBRK0451

NetBotz Rack Monitor 450 (with 120/240V Power Supply)



Overview

Presentation	Supports up to 2 external camera pods, 2 sensor pods and up to 18 Universal Sensors.
Lead time	Usually in Stock



General

Provided equipment	Country-specific detachable power cord Documentation CD Installation guide Rack Mounting brackets Temperature/Humidity Sensor
Number of Sensor Pods Supported	2
Number of Universal Sensors Supported	18

Physical

Maximum Depth	3.66 in (9.3 cm)
Maximum Height	1.69 in (4.3 cm)
Mounting location	Front
Net Weight	3.84 lb(US) (1.74 kg)
Maximum Width	17.01 in (43.2 cm)

Conformance

Standards	FCC Part 15 class A ICES-003
Product certifications	AS/NZS 3548 (C-Tick) Class A CUL Listed CE GOST IRAM Low Voltage Directive 2006/95/EC NOM UL Listed VCCI Class A VDE

Environmental

Ambient air temperature for operation	32...113 °F (0...45 °C)
Operating altitude	0...10000 ft
Relative humidity	0...95 %
Ambient air temperature for storage	5...149 °F (-15...65 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)

Communications & Management

Communication network type	RJ-45 10/100 Base-T
Communication port protocol	DHCP DNS HTTP HTTPS SMTP SOCKS TCP/IP


Ordering and shipping details

GTIN	03606485441023
Package weight(Lbs)	6.31 lb(US) (2.86 kg)

Packing Units

Package 1 Height	7.48 in (19 cm)
Package 1 width	30.75 in (78.1 cm)
Package 1 Length	14.53 in (36.9 cm)

Offer Sustainability

EU RoHS Directive	Under investigation
Mercury free	Yes
RoHS exemption information	 Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------