

PSSu E F 2DO 2-T

314215



Electronic module digital inputs and outputs, with failsafe function, 2 outputs 1-pole (2 A), exp. temperature.

Technical details

| | |
|--------------------------------------|---|
| Certifications: | CE;cULus Listed;EAC (Eurasian);TÜV;KOSHA |
| Application range: | Failsafe |
| Positive switching 1-pole SC output: | 2 |
| Protection type, housing: | IP20 |
| Permitted base modules: | PSSu BP 1/12C-T;PSSu BP 1/12S-T;PSSu BP 1/8C-T;PSSu BP 1/8S-T;PSSu BP-C 1/8C-T;PSSu BP-C 1/8S-T;PSSu BP-C1 1/12C-T;PSSu BP-C1 1/12S-T |
| Width dimension: | 12.6 mm |
| Height dimension: | 76.0 mm |
| Depth dimension: | 60.2 mm |
| Gross weight: | 44 g |
| Net weight: | 36 g |
| Ambient temperature: | -40 - 70 °C |

Accessories



314600

PSSu BP 1/8 S-T



314601

PSSu BP 1/8 C-T



314610

PSSu BP-C 1/8 S-T



314611

PSSu BP-C 1/8 C-T



314618

PSSu BP 1/12 S-T



314622

PSSu BP-C1 1/12 S-T



314623

PSSu BP-C1 1/12 C-T

Optional accessories



312900

PSSu A ET (10 pcs.)



312901

PSSu A ETM (2 pcs.)



312949

PSSu A ET PE (10 pcs.)



312958

PSSu A LA0 (10 x 108 pcs.)



312967

PSSu A LA0.1 (10 x 108 pcs.)



314902

PSSu A EC-T