TE Internal #: T4052218004-006


M8/M12 Cable Assemblies, Sensor/Actuator, 4 Positions, A M8 /M12 Cable Assembly Keying, Plug/Receptacle, M8 to M12, Cable

Assembly Length 7000 mm

View on TE.com >



Cable Assemblies > Copper Cable Assemblies > M8/M12 Cable Assemblies > M8 MR - M12 FR CABLE ASSEMBLY



M8/M12 Application Type: Sensor/Actuator

Number of M8/M12 Cable Assembly Positions: 4

M8/M12 Cable Assembly Keying: A

M8/M12 Cable Assembly Connector Type: Plug/Receptacle

M8/M12 Cable Assembly Type: M8 to M12

All M8 MR - M12 FR CABLE ASSEMBLY (28)

Features

Product Type Features

LED	Without
Product Type	Cable Assembly
Cable Type	PVC
Assembly Type	Pigtail
M8/M12 Cable Assembly Connector Type	Plug/Receptacle
M8/M12 Cable Assembly Type	M8 to M12
M8/M12 Cable Assembly Shielded	No
Configuration Features	
Number of M8/M12 Cable Assembly Positions	4
M8/M12 Cable Assembly Keying	A
M8/M12 Cable Assembly Configuration	Double Ended
Electrical Characteristics	

30 VDC

Operating Voltage



Body Features

body i catales	
Environmental Protection	With
Conductor Material	Copper Alloy
Connector Color	Blue
Wire Color	Brown-White-Blue-Black
Insulation Material	PVC
Cable Jacket Color	Black
Contact Features	
Contact Current Rating	3 A
Mechanical Attachment	
Screw & Hole Thread Size	M8 x M12
Housing Features	
M8/M12 Cable Assembly Housing Material	GF Nylon
Dimensions	
Dimensions Overall Outside Cable Diameter	4.5 mm
	4.5 mm .25 mm ²
Overall Outside Cable Diameter	
Overall Outside Cable Diameter Wire Size	.25 mm²
Overall Outside Cable Diameter Wire Size Cable Assembly Length	.25 mm²
Overall Outside Cable Diameter Wire Size Cable Assembly Length Usage Conditions	.25 mm ² 7000 mm
Overall Outside Cable Diameter Wire Size Cable Assembly Length Usage Conditions Operating Temperature Range	.25 mm ² 7000 mm
Overall Outside Cable Diameter Wire Size Cable Assembly Length Usage Conditions Operating Temperature Range Operation/Application	.25 mm ² 7000 mm -25 - 85 °C[-13 - 185 °F]
Overall Outside Cable Diameter Wire Size Cable Assembly Length Usage Conditions Operating Temperature Range Operation/Application M8/M12 Application Type	.25 mm ² 7000 mm -25 - 85 °C[-13 - 185 °F]
Overall Outside Cable Diameter Wire Size Cable Assembly Length Usage Conditions Operating Temperature Range Operation/Application M8/M12 Application Type Packaging Features	.25 mm ² 7000 mm -25 - 85 °C[-13 - 185 °F] Sensor/Actuator

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant with Exemptions
EU ELV Directive 2000/53/EC	Not Yet Reviewed
China RoHS 2 Directive MIIT Order No 32, 2016	Restricted Materials Above Threshold



EU REACH Regulation (EC) No. 1907/2006

Current ECHA Candidate List: JUN 2020

(209)

Candidate List Declared Against: JAN 2020

(205)

SVHC > Threshold:

Pb (1.9% in Pb-Alloy in Copper)

Article Safe Usage Statements:

Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Recycle if possible and dispose of the article by following all applicable governmental regulations relevant to your geographic location.

Halogen Content

Not Yet Reviewed for halogen content

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Customers Also Bought





















Documents

Product Drawings

RPC-M8-4MR-7.0-M12-4FR-PVC

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_T4052218004-006_1.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_T4052218004-006_1.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_T4052218004-006_1.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Specifications

Application Specification

English

Application Specification

English