



ENGLISH

Datasheet

Stock No. 161-7253

RS PRO Horizontal PDU 4 BS socket 3m BS Plug



10/11/2017

BS1363 13A plug



SPECIFICATIONS:

Product Name: Designated Power Distribution Unit for Cabinet

Socket Type: BS1363 (90degree) Outlet Module

Socket Quantity: 4

Power Input: Left end single input

Bracket Install: Frontal installation

Cable with plug: BS1363 13A plug

Control Function: No controlling function

Protection Function: 2017 hot swaps module base

Case: Black

Cable Specification: 3 x 1.5 mm² x 3M

Product Size: L x W x H =485 x 44.4 x 62 mm

Mounting Length: 458mm

Case Length: 428mm

Fittings: 2pcs $\phi 6 \times 16$ mm cross bolt, 2pcs M6 float nut, PDU manual, 1pc 155mm cover plate

Electrical Characteristics:

Rating voltage: 250VAC 50/60Hz

10/11/2017

Rating Current: 13A

Max. Power: 3250W

Safety Authentication: CE

Operating Temperature: 0~50°C, relative humidity 0-95%

Applications:

PDU - Power Distribution Unit is widely used in network enclosure and server rack of data center in field of information technology,telecom, electric, power, finance and insurance,aviation,transportation,hospital,education,E-government,etc.