

Non-Fusible Safety Switches

P&S Non-Fusible Safety Switches feature extra-tough components, including an impact-resistant Valox® NEMA 4X enclosure. And an innovative design that delivers safe, sure operation under the worst conditions. These rugged performers are available in capacities from 30 to 100 amps.




FEATURES & BENEFITS

Compact design fits in most I-beams to provide mounting versatility, easy access, and reduced possibility of impact damage.

Nonconductive, watertight, corrosion, heat, and impact-resistant thermoplastic enclosure ensures NEMA 4X and 12 ratings. Withstands the harshest industrial environments.

Optional auxiliary contacts for use with PLCs and pilot lights.

Durable, stainless steel cover-retaining chain makes installation and maintenance more convenient.



PS30SS

Heavy-duty, ergonomic switch handle meets OSHA Lockout/Tagout provisions and provides plenty of grip for sure, easy operation.

Adjustable mounting feet can be moved to the center of the unit for instant strut- or pole-mounting without special brackets or harnesses.

FIELD USES/VERTICAL MARKETS

- Food & Beverage
- Pulp & Paper Mills
- Mines
- Refrigeration
- Petrochemical
- Water/Waste Water
- Shipbuilding
- Temporary Power



PASS & SEYMOUR®

IEC 309 Industrial Products

Non-Fusible Safety Switches

ORDERING INFORMATION

NON-FUSIBLE SAFETY SWITCHES

VOLTAGE	MAXIMUM HORSEPOWER RATING	NON-FUSIBLE SAFETY SWITCH CATALOG #	NON-FUSIBLE SAFETY SWITCH WITH AUXILIARY CONTACT** CATALOG #	NON-FUSIBLE SAFETY SWITCH WITH 3 AUXILIARY CONTACTS** CATALOG #	AUXILIARY CONTACT KIT*	REPLACEMENT SWITCH	REPLACEMENT SWITCH WITH AUXILIARY CONTACT	REPLACEMENT COVER
30 AMPS 600VAC								
120VAC	1 HP	PS30SS	PS30SSAX	PS30SSAX3	AX30	RS30	PS30RSAX	PS30SSRC
208VAC	2 HP							
240VAC	3 HP							
277VAC	3 HP							
480VAC	5 HP							
3ø 240VAC	5 HP							
3ø 480VAC	10 HP							
3ø 600VAC	10 HP							
3øY 120/208VAC	5 HP							
3øY 277/480VAC	10 HP							
3øY 347/600VAC	10 HP							
60 AMPS 600VAC								
120VAC	3 HP	PS60SS	PS60SSAX	N/A	AX60	RS60	Contact Customer Support	PS60SSRC
208VAC	10 HP							
240VAC	10 HP							
277VAC	15 HP							
480VAC	20 HP							
3ø 240VAC	20 HP							
3ø 480VAC	40 HP							
3ø 600VAC	50 HP							
3øY 120/208VAC	20 HP							
3øY 277/480VAC	40 HP							
3øY 347/600VAC	50 HP							
100 AMPS 600VAC								
120VAC	5 HP	PS100SS	PS100SSAX	N/A	AX60	Contact Customer Support	Contact Customer Support	PS100SSRC
208VAC	10 HP							
240VAC	15 HP							
277VAC	15 HP							
480VAC	30 HP							
3ø 240VAC	25 HP							
3ø 480VAC	50 HP							
3ø 600VAC	50 HP							
3øY 120/208VAC	20 HP							
3øY 277/480VAC	50 HP							
3øY 347/600VAC	50 HP							

* For replacement of side mount auxiliary contact on previous design.
 **Auxiliary contacts break before switch contacts break for use with VFD.

For more information on these and other P&S products refer to our Catalog or visit our web site.

PASS & SEYMOUR®

IEC 309 Industrial Products

Non-Fusible Safety Switches



TECHNICAL SPECIFICATIONS

3rd Party Compliance

CULus listed to per CSA specifications C22.2.
Meets NEC Article 430 as well as UL508 standards.

- Manufacturer's Identification PS60SS
- Description: Non-Fusible Safety Switch
- Rating: 60A, 600VAC maximum
- Enclosure Type: NEMA 4X (watertight, hosedown), 12K (dusttight, falling dirt), IP67 suitability
- Conduit Location: Top, bottom, or back feed. Units are shipped without holes for conduit. Spot drills for locating hole saw or knockouts are provided for top, bottom, or back feed. End user decides at installation whether top, bottom, or back feed is appropriate. No closure plug kits required. Units are not provided with conduit hubs.

MATERIALS

Enclosure Cover	Valox 357®
Enclosure Base	Valox 357®
Enclosure Gasket	Neoprene
Switch Handle	Valox 357®
Switch Handle Seal	Neoprene
Switch Key	10% Glass-Filled Nylon
Mounting Feet	Valox 357®
Mounting Feet Screws	300 Series Stainless Steel
Enclosure Assembly Screws	300 Series Stainless Steel
Enclosure Assembly Inserts	Brass (60 and 100 amp units only)
Grounding Plate	Galvanized Steel
Cover Chain	300 Series Stainless Steel

PERFORMANCE


Electrical:	
Dielectric Voltage Withstand	3000V minimum
Maximum Working Voltage	600V RMS
Current Interrupting	Listed for current interrupting at full-rated current and voltage
Short Circuit Withstand Rating	For use on circuit capable of delivering not more than (see chart below) RMS amps at 600VAC
Operations	Mechanical: 15,000 cycles Electrical: 10,000 cycles
Auxiliary Contacts (optional)	10A @ 600VAC 1 N.O. & 1 N.C.
Mechanical:	
Impact Resistance	Per UL746C
Terminal Identification	Per UL and CSA
Product Identification	Identification and rating on external and internal labels
Mounting	External adjustable feet with five (5) positions Can be mounted directly to channel or strut (no washers required)
Environmental:	
Moisture Resistance	Per UL50, section 35, NEMA Enclosure Type 4X (watertight, hosedown) Per UL50, section 35, NEMA Enclosure Type 12K (dusttight, falling dirt) • IP67 suitability
Flammability	UL94 5VA and VO Classification
Operating Temperature	Maximum continuous: +60°C • Minimum continuous: -50°C without impact
UV Resistance	All enclosure materials are UV stable

TECHNICAL SPECIFICATIONS

NON-FUSIBLE SAFETY SWITCHES DIMENSIONS

Amps	A	B	C	D	E	F	G	H	I	J	K
30	5.75	7.38	4.88	7.19	9.69	3.75	5.75	6.56	6.13	8.06	8.88
60	7.19	9.13	6.31	9.63	12.38	4.75	7.19	8.13	8.00	10.38	11.38
100	7.19	9.13	6.31	9.63	12.38	4.75	7.19	8.13	8.00	10.38	11.38

All measurements shown in inches.



(See dimensions above.)

Warranty

1 Year

COO

US

ALSO AVAILABLE...

- Hospital Grade Devices
- PlugTail® Devices
- SPD & Isolated Ground Devices
- Ground Continuity Monitoring (GCM)
- Straight Blade Plugs & Connectors
- Turnlok® Locking Devices
- Weatherproof Boxes & Covers
- IEC 309 Industrial Products
- Flexcor® Wire Mesh Grips



Electrical Wiring Systems

P.O. Box 4822
Syracuse, NY 13221-4822
Phone: 1.800.776.4035
www.legrand.us/passandseymour

570 Applewood Crescent
Vaughan, Ontario L4K 4B4
Phone: 905.738.9195
www.legrand.ca