

## PNOZ X7.1 24VAC/DC 1n/o 1n/c

774051



Safety relay (standalone) Inputs: Single-channel wiring Outputs: 1 N/O, 1 N/C. Automatic/manual reset UB 24 V AC/DC, width: 22.5 mm, integral screw terminals, Monitoring E-STOP, safety gates.

### Technical details

|  |  |
|--|--|
| Certifications:                          | CE;cULus Listed;EAC (Eurasian);TÜV;CCC                           |
| Application options:                     | Instantaneous E-STOP monitoring;Limit switch;Safety gate monitor |
| Operating modes:                         | Single-channel;Automatic reset;Manual reset                      |
| Product standard:                        | EN 60947-5-1   |
| Standards:                               | EN 60204-1;EN 62061;EN ISO 13849-1;VDE 0113-1                    |
| Supply voltage (V):                      | 24,0   |
| Supply voltage type:                     | AC/DC  |
| Terminal style:                          | fixed  |
| Terminal type:                           | Screw terminal   |
| Number of instantaneous safety contacts: | 1  |
| Number of delayed safety contacts:       | 0  |
| Number of auxiliary contacts:            | 1  |
| Number of semiconductor outputs:         | 0  |
| Stop category:                           | 0  |
| Max. current at DC13 I (6 cycles/min):   | 6.0 A  |
| Max. current at AC15:                    | 5.0 A  |
| Width dimension:                         | 22.5 mm  |
| Height dimension:                        | 87.0 mm  |
| Depth dimension:                         | 121.0 mm   |
| Gross weight:                            | 195 g  |

|                      |             |
|----------------------|-------------|
| Net weight:          | 185 g       |
| Ambient temperature: | -10 - 55 °C |