



### Overview

Lead time	Usually in Stock
-----------	------------------

### General

Provided equipment	User manual USB cable
Number of tare power	25 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
UPS size	WS

### Physical

Cable length	6 ft (1.83 m)
Color	Black
Depth	12.20 in (31 cm)
Height	7.48 in (19 cm)
Mounting preference	No preference
Net Weight	15.87 lb(US) (7.2 kg)
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No
Maximum Width	3.58 in (9.1 cm)

### Input

Input Frequency	60 Hz +/- 3 Hz
Plug standard	NEMA 5-15P
Efficiency at full load	88...139 V
Maximum Input Current per phase	12 A
Switching current capacity	15 A
Number of cables	1
Nominal Input Voltage	120 V

## Output

Kw Rating	600 W
Max Configurable Power (Watts)	600 W
Output frequency	60 Hz sync to mains
Topology	Line Interactive
Waveform Type	Stepped approximation to a sinewave
Nb of power socket outlets	4 NEMA 5-15R 4 NEMA 5-15R surge
Curve equation	Efficiency
Curve fixed loss	0.0039
Curve load maximum	100 %
Curve load minimum	1 %
Curve proportional loss	0
Curve square loss	0.0065
Curve X-axis maximum	100 %
Curve test cond ID	Curve fit of data measured in accordance with the US DOE Test Procedure for Uninterruptible Power Supplies. All measurements taken in normal mode(s), at typical environmental conditions, with 120V/60Hz electrical input and balanced resistive load (PF = 1.0) output.
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Graph display	1
Maximum output current	15 A
Output voltage	120 V
Maximum configurable power in VA	1000 VA
Rated power in VA	1000 VA
Transfer Time	8ms typical : 10 ms maximum

## Conformance

Product certifications	California (CEC) Battery Charger ENERGY STAR V2.0 (USA) TUV C-US certified
Standards	FCC Part 15 class B
Equipment protection policy	Lifetime : \$250000

## Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Relative humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient air temperature for storage	5...113 °F (-15...45 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)
Acoustic level	45 dBA
Heat dissipation	48.5 Btu/h
Show note OP temperature	No

## Batteries & Runtime

Battery type	Lead-Acid battery
Included Battery Modules	1
Battery Slots Empty	0
Typical recharge time	12 h
RBC Quantity	1
Liquid Electrolyte Value	0
Battery curve	C
Battery Charge Power (Watts)	12 W rated
Battery power in VAH	140 VAh capacity 140 VAh runtime
Battery life	3...5 year(s)
Extendable Run Time	0

## Communications & Management

Control panel	Multi-function LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

## Surge Protection and Filtering

Surge energy rating	1103 J
Filtering	Full time multi-pole noise filtering : 5% IEEE surge let-through : zero clamping response time : mee
Data line protection	Network line - 10/100/1000 Base-T Ethernet (RJ45 connector) Coaxial cable for CATV/SATV/modem/Audio-Video (coax connector)





## Ordering and shipping details

GTIN	00731304331766
Package weight(Lbs)	17.64 lb(US) (8 kg)

## Packing Units

Package 1 Height	9.96 in (25.3 cm)
Package 1 width	5.59 in (14.2 cm)
Package 1 Length	17.40 in (44.2 cm)
SCC14	10731304331763
Number of Units in Package 2	2
Package 2 Weight	37.04 lb(US) (16.80 kg)
Package 2 Height	11 in (279.40 mm)
Package 2 width	12 in (304.80 mm)
Package 2 Length	18 in (457.20 mm)
Number of Units in Package 3	70

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
Energy Star	 <a href="#">ENERGY STAR UPS V1.0 (USA)</a>
REACH Regulation	 <a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	 Yes

Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
Optimized Energy Efficiency	Energy efficient product
<b>Contractual warranty</b>	
Warranty	3 years repair or replace