



Overview

Presentation	Universal sensor that monitors temperature and humidity in your Data Center or Network Closet.
Lead time	Usually in Stock

General

Provided equipment	Humidity sensor Installation guide Temperature Sensor
--------------------	-------------------------------------------------------------

Physical

Color	Black
Depth	0.20 in (0.5 cm)
Height	0.24 in (0.6 cm)
Net Weight	0.40 lb(US) (0.18 kg)
Maximum Width	0.20 in (0.5 cm)

Environmental

Ambient air temperature for operation	32...131 °F (0...55 °C)
Operating altitude	0...10000 ft
Relative humidity	0...95 %
Ambient air temperature for storage	5...149 °F (-15...65 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)

Ordering and shipping details

Category	09305 - INDUSTRIAL UPS
GTIN	00731304234005
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	No

Packing Units

Package 1 Height	0.39 in (1 cm)
Package 1 width	10.00 in (25.4 cm)
Package 1 Length	5.98 in (15.2 cm)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Lead free	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Halogen content performance	Halogen free product

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------