

# NET9RMBLK

## APC Black Rackmount Performance SurgeArrest 9 Outlet 120V



### Overview

|           |                  |
|-----------|------------------|
| Lead time | Usually in Stock |
|-----------|------------------|



### General

|                    |  |
|--------------------|--|
| Provided equipment | Cord management rails<br>Plug pull protectors<br>Rack Mounting brackets<br>User Manual |
|--------------------|--|

### Physical

|               |                       |
|---------------|-----------------------|
| Cable length  | 15 ft (4.57 m)        |
| Color         | Black                 |
| Depth         | 5.75 in (14.6 cm)     |
| Height        | 1.73 in (4.4 cm)      |
| Net Weight    | 4.81 lb(US) (2.18 kg) |
| Maximum Width | 19.02 in (48.3 cm)    |

### Input

|                                 |                                |
|---------------------------------|--------------------------------|
| Maximum Line Current per phase  | 15 A                           |
| Input Frequency                 | 50/60 Hz +/- 5 Hz auto-sensing |
| Plug standard                   | NEMA 5-15P                     |
| Maximum Input Current per phase | 15 A                           |
| Switching current capacity      | 15 A                           |
| Nominal Input Voltage           | 120 V                          |

### Output

|                                |            |
|--------------------------------|------------|
| Number of power socket outlets | 9          |
| Outlet standard                | NEMA 5-15R |

### Conformance

|                             |                    |
|-----------------------------|--------------------|
| UL 1449 TVSS Rating         | 330                |
| Product certifications      | CSA<br>UL Listed   |
| Standards                   | UL 1283<br>UL 1449 |
| Equipment protection policy | Lifetime : \$25000 |

## Environmental

|                                       |                                  |
|---------------------------------------|----------------------------------|
| Ambient air temperature for operation | 32...104 °F (0...40 °C)          |
| Relative humidity                     | 0...95 %                         |
| Operating altitude                    | 0...10000 ft                     |
| Ambient air temperature for storage   | 5...113 °F (-15...45 °C)         |
| Storage altitude                      | 0...50000 ft (0.00...15240.00 m) |

## Surge Protection and Filtering

|                             |  |
|-----------------------------|--|
| NM Surge Response Time (ns) | 0 ns common mode                       |
| Common mode rejection       | 90 dB                                  |
| Peak current                | 40 KA common mode<br>26 kA normal mode |
| Surge energy rating         | 2770 J                                 |

## Ordering and shipping details

|                     |                       |
|---------------------|-----------------------|
| GTIN                | 00731304248620        |
| Package weight(Lbs) | 6.11 lb(US) (2.77 kg) |

## Packing Units

|                              |                        |
|------------------------------|------------------------|
| Package 1 Height             | 2.76 in (7 cm)         |
| Package 1 width              | 19.02 in (48.3 cm)     |
| Package 1 Length             | 13.50 in (34.3 cm)     |
| SCC14                        | 10731304248627         |
| Number of Units in Package 2 | 6                      |
| Package 2 Weight             | 28.9 lb(US) (13.11 kg) |
| Package 2 Height             | 21 in (533.40 mm)      |
| Package 2 width              | 10 in (254.00 mm)      |
| Package 2 Length             | 15 in (381.00 mm)      |

## Offer Sustainability

|                           |   |
|---------------------------|---|
| California proposition 65 | WARNING: This product can expose you to chemicals including: 1,3-Butadiene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation          | <a href="#">REACH Declaration</a>   |
| EU RoHS Directive         | Compliant <a href="#">EU RoHS Declaration</a>   |

## Contractual warranty

|          |          |
|----------|----------|
| Warranty | Lifetime |
|----------|----------|