



### Overview

|           |                  |
|-----------|------------------|
| Lead time | Usually in Stock |
|-----------|------------------|

### Physical

|               |                       |
|---------------|-----------------------|
| Cable length  | 6 ft (1.83 m)         |
| Depth         | 13.70 in (34.8 cm)    |
| Height        | 1.18 in (3 cm)        |
| Net Weight    | 1.19 lb(US) (0.54 kg) |
| Maximum Width | 2.05 in (5.2 cm)      |

### Input

|                                 |            |
|---------------------------------|------------|
| Maximum Line Current per phase  | 15 A       |
| Input Frequency                 | 50/60 Hz   |
| Plug standard                   | NEMA 5-15P |
| Maximum Input Current per phase | 15 A       |
| Switching current capacity      | 15 A       |
| Nominal Input Voltage           | 120 V      |

### Output

|                                |            |
|--------------------------------|------------|
| Number of power socket outlets | 6          |
| Outlet standard                | NEMA 5-15R |

### Conformance

|                             |   |
|-----------------------------|---|
| Product certifications      | MET Canada<br>MET USA                     |
| Standards                   | FCC Part 15 class B<br>UL 1363<br>UL 1449 |
| Equipment protection policy | Lifetime : \$50000                        |

### Environmental

|                                       |                                  |
|---------------------------------------|----------------------------------|
| Ambient air temperature for operation | 32...104 °F (0...40 °C)          |
| Relative humidity                     | 0...95 % non-condensing          |
| Operating altitude                    | 0...10000 ft                     |
| Ambient air temperature for storage   | 5...113 °F (-15...45 °C)         |
| Storage altitude                      | 0...50000 ft (0.00...15240.00 m) |

## Surge Protection and Filtering

|                             |  |
|-----------------------------|--|
| NM Surge Response Time (ns) | 1 ns common mode                       |
| Common mode rejection       | 40 dB                                  |
| Peak current                | 48 KA common mode<br>24 kA normal mode |
| Surge energy rating         | 1080 J                                 |

## Ordering and shipping details

|                     |                       |
|---------------------|-----------------------|
| GTIN                | 00731304328933        |
| Package weight(Lbs) | 1.41 lb(US) (0.64 kg) |

## Packing Units

|                              |                       |
|------------------------------|-----------------------|
| Package 1 Height             | 1.57 in (4 cm)        |
| Package 1 width              | 4.53 in (11.5 cm)     |
| Package 1 Length             | 14.96 in (38 cm)      |
| SCC14                        | 10731304328930        |
| Number of Units in Package 2 | 6                     |
| Package 2 Weight             | 9.35 lb(US) (4.24 kg) |
| Package 2 Height             | 10 in (254.00 mm)     |
| Package 2 width              | 6 in (152.40 mm)      |
| Package 2 Length             | 16 in (406.40 mm)     |
| Number of Units in Package 3 | 360                   |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| Sustainable offer status   | Green Premium product   |
| California proposition 65  | WARNING: This product can expose you to chemicals including: 1,3-Butadiene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| REACH Regulation           | <a href="#">REACH Declaration</a>   |
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a>   |
| Lead free                  | Yes   |
| Mercury free               | Yes   |
| RoHS exemption information | <a href="#">Yes</a>   |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>   |
| Circularity Profile        | <a href="#">End Of Life Information</a>   |

## Contractual warranty

|          |          |
|----------|----------|
| Warranty | Lifetime |
|----------|----------|