



### Overview

Lead time	Usually in Stock
-----------	------------------

### General

Provided equipment	Documentation CD Installation guide Warranty card
--------------------	---

### Physical

Color	Black
Depth	26.88 in (68.27 cm)
Height	17.01 in (43.2 cm)
Net Weight	200.62 lb(US) (91 kg)
Maximum Width	5.12 in (13 cm)

### Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Operating altitude	0...10000 ft
Relative humidity	0...95 % non-condensing
Ambient air temperature for storage	5...113 °F (-15...45 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)

### Batteries & Runtime

Battery Slots Empty	0
Included Battery Modules	0
Device mounting	Stand alone battery stack
Battery voltage	+/- 192 V
Battery type	Lead-Acid battery
RBC Quantity	2

### Ordering and shipping details

GTIN	00731304292746
Package weight(Lbs)	223.77 lb(US) (101.5 kg)

## Packing Units

Package 1 Height	16.54 in (42 cm)
Package 1 width	23.62 in (60 cm)
Package 1 Length	39.37 in (100 cm)
Number of Units in Package 3	1

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------