



Overview

| | |
|-----------|------------------|
| Lead time | Usually in Stock |
|-----------|------------------|



General

| | |
|--------------------|-------------|
| Provided equipment | User manual |
|--------------------|-------------|

Physical

| | |
|---------------|-----------------------|
| Cable length | 8 ft (2.44 m) |
| Color | Black |
| Depth | 11.89 in (30.2 cm) |
| Height | 1.57 in (4 cm) |
| Net Weight | 2.23 lb(US) (1.01 kg) |
| Maximum Width | 4.69 in (11.9 cm) |

Input

| | |
|----------------------------|------------|
| Input Frequency | 50/60 Hz |
| Plug standard | NEMA 5-15P |
| Switching current capacity | 15 A |
| Nominal Input Voltage | 120 V |

Output

| | |
|--------------------------------|------------|
| Number of power socket outlets | 11 |
| Outlet standard | NEMA 5-15R |

Conformance

| | |
|-----------------------------|----------------------------------|
| UL 1449 TVSS Rating | L-N: 400 L-G: 500 N-G: 500 |
| Product certifications | MET Canada MET USA |
| Equipment protection policy | Lifetime : \$250000 |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environmental

| | |
|---------------------------------------|----------------------------------|
| Ambient air temperature for operation | 32...113 °F (0...45 °C) |
| Relative humidity | 0...95 % |
| Operating altitude | 0...10000 ft |
| Ambient air temperature for storage | 5...113 °F (-15...45 °C) |
| Storage altitude | 0...50000 ft (0.00...15240.00 m) |

Surge Protection and Filtering

| | |
|-----------------------------|--|
| NM Surge Response Time (ns) | 1 ns common mode |
| Common mode rejection | 25 dB |
| Peak current | 20 KA common mode 60 kA normal mode |
| Surge energy rating | 2880 J |

Ordering and shipping details

| | |
|---------------------|-----------------------|
| Package weight(Lbs) | 2.47 lb(US) (1.12 kg) |
|---------------------|-----------------------|

Packing Units

| | |
|------------------------------|------------------------|
| Package 1 Height | 2.36 in (6 cm) |
| Package 1 width | 7.48 in (19 cm) |
| Package 1 Length | 13.39 in (34 cm) |
| SCC14 | 10731304322990 |
| Number of Units in Package 2 | 12 |
| Package 2 Weight | 31.2 lb(US) (14.15 kg) |
| Package 2 Height | 15.75 in (400.05 mm) |
| Package 2 width | 14 in (355.60 mm) |
| Package 2 Length | 14.75 in (374.65 mm) |
| Number of Units in Package 3 | 216 |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: 1,3-Butadiene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| Environmental Disclosure | Product Environmental Profile |
| Circularity Profile | End Of Life Information |

Contractual warranty

| | |
|----------|----------|
| Warranty | Lifetime |
|----------|----------|