



Overview

Lead time	Usually in Stock
-----------	------------------

Physical

Cable length	6 ft (1.83 m)
Depth	5.20 in (13.2 cm)
Height	5.31 in (13.5 cm)
Net Weight	1.52 lb(US) (0.69 kg)
Maximum Width	2.72 in (6.9 cm)

Input

Maximum Line Current per phase	15 A
Input Frequency	50/60 Hz
Plug standard	NEMA 5-15P
Maximum Input Current per phase	15 A
Switching current capacity	15 A
Nominal Input Voltage	120 V

Output

Number of power socket outlets	6
Outlet standard	NEMA 5-15R

Conformance

Product certifications	CULus
Standards	FCC Part 15 class B UL 1310 UL 1363 UL 1449
Equipment protection policy	Lifetime : \$50000

Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Relative humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient air temperature for storage	5...113 °F (-15...45 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)

Surge Protection and Filtering

NM Surge Response Time (ns)	1 ns common mode
Common mode rejection	40 dB
Peak current	48 KA common mode 24 kA normal mode
Surge energy rating	1080 J

Ordering and shipping details

Package weight(Lbs)	1.70 lb(US) (0.77 kg)
---------------------	-----------------------

Packing Units

Package 1 Height	5.43 in (13.8 cm)
Package 1 width	4.72 in (12 cm)
Package 1 Length	6.73 in (17.1 cm)
SCC14	10731304343742
Number of Units in Package 2	6
Package 2 Weight	12.08 lb(US) (5.48 kg)
Package 2 Height	7.48 in (189.99 mm)
Package 2 width	12.52 in (318.01 mm)
Package 2 Length	16.14 in (409.96 mm)
Number of Units in Package 3	192

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	Lifetime
----------	----------