



### Overview

Lead time	Usually in Stock
-----------	------------------

### General

Provided equipment	Installation guide
--------------------	--------------------

### Physical

Color	Black
Depth	22.44 in (57 cm)
Height	7.76 in (19.7 cm)
Net Weight	33.71 lb(US) (15.29 kg)
Maximum Width	12.20 in (31 cm)

### Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Operating altitude	0...10000 ft
Relative humidity	0...95 % non-condensing
Ambient air temperature for storage	5...113 °F (-15...45 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)

### Batteries & Runtime

Battery Slots Empty	0
Included Battery Modules	0
Device mounting	Enclosed battery cartridge
Battery type	Lead-Acid battery
RBC Quantity	1

### Ordering and shipping details

Package weight(Lbs)	38.69 lb(US) (17.55 kg)
---------------------	-------------------------

### Packing Units

Package 1 Height	7.99 in (20.3 cm)
Package 1 width	13.50 in (34.3 cm)
Package 1 Length	25.00 in (63.5 cm)
Number of Units in Package 3	12

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
Energy Star	<a href="#">ENERGY STAR UPS V1.0 (USA)</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>

## Contractual warranty

Warranty	1 year repair or replace
----------	--------------------------