



Overview

Lead time	Usually in Stock
-----------	------------------

Physical

Cable length	6 ft (1.83 m)
Color	Black
Depth	12.99 in (33 cm)
Height	1.26 in (3.2 cm)
Net Weight	2.03 lb(US) (0.92 kg)
Maximum Width	3.50 in (8.9 cm)

Input

Input Frequency	50/60 Hz
Plug standard	NEMA 5-15P
Switching current capacity	15 A
Nominal Input Voltage	120 V

Output

Number of power socket outlets	8
Outlet standard	NEMA 5-15R

Conformance

UL 1449 TVSS Rating	L-N: 400 L-G: 500 N-G: 500
Product certifications	CSA
Standards	UL 1363 UL 1449
Equipment protection policy	Lifetime : \$150000

Environmental

Ambient air temperature for operation	32...113 °F (0...45 °C)
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	5...113 °F (-15...45 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)

Surge Protection and Filtering

EP Joule Rating	2525 J
Data Lines Protected (multi-line only)	1-4
NM Surge Response Time (ns)	0 ns common mode
Common mode rejection	70 dB
Surge energy rating	2770 J
Data line protection	RJ11 2-Way Modem/Fax/DSL splitter with protection (four wire dual lines) Cable modem/video protection

Ordering and shipping details

GTIN	00731304249047
Package weight(Lbs)	2.43 lb(US) (1.1 kg)

Packing Units

Package 1 Height	2.36 in (6 cm)
Package 1 width	5.59 in (14.2 cm)
Package 1 Length	14.17 in (36 cm)
SCC14	10731304249044
Number of Units in Package 2	6
Package 2 Weight	16.5 lb(US) (7.48 kg)
Package 2 Height	12 in (304.80 mm)
Package 2 width	8 in (203.20 mm)
Package 2 Length	15 in (381.00 mm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: 1,3-Butadiene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	Lifetime
----------	----------