



Overview

Lead time	Usually in Stock
-----------	------------------

General

Provided equipment	User manual USB cable Coaxial cable RCBO
Number of tare power	11 W
Number of power module free slots	0
Number of power module filled slots	0
Redundant	No
UPS size	WS

Physical

Cable length	6 ft (1.83 m)
Depth	15.04 in (38.2 cm)
Height	9.84 in (25 cm)
Mounting preference	No preference
Net Weight	24.25 lb(US) (11 kg)
Mounting mode	Not rack-mountable
Two post mountable	0
USB compatible	No
Maximum Width	3.94 in (10 cm)

Input

Input Frequency	60 Hz +/- 3 Hz
Plug standard	NEMA 5-15P
Efficiency at full load	88...139 V
Maximum Input Current per phase	12 A
Switching current capacity	15 A
Nominal Input Voltage	120 V

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Output

Kw Rating	900 W
Max Configurable Power (Watts)	900 W
Output frequency	60 Hz sync to mains
Topology	Line Interactive
Waveform Type	Stepped approximation to a sine wave
Nb of power socket outlets	5 NEMA 5-15R 5 NEMA 5-15R surge
Curve equation	Efficiency
Curve fixed loss	0.0032
Curve load maximum	100 %
Curve load minimum	1 %
Curve proportional loss	0
Curve square loss	0.0082
Curve X-axis maximum	100 %
Curve test cond ID	Curve fit of data measured in accordance with the US DOE Test Procedure for Uninterruptible Power Supplies. All measurements taken in normal mode(s), at typical environmental conditions, with 120V/60Hz electrical input and balanced resistive load (PF = 1.0) output.
Curve X-axis minimum	0 %
Curve X-axis title	Load
Curve X-axis units	Percentage
Curve Y-axis maximum	100 %
Curve Y-axis minimum	50 %
Curve Y-axis title	Efficiency
Curve Y-axis units	Percentage
Graph display	1
Output voltage	120 V
Maximum configurable power in VA	1500 VA
Rated power in VA	1500 VA
Transfer Time	8ms typical : 10 ms maximum

Conformance

Product certifications	California (CEC) Battery Charger ENERGY STAR V2.0 (USA) TUV C-US certified
Standards	FCC Part 15 class B
Equipment protection policy	Lifetime : \$250000

Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	5...104 °F (-15...40 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)
Acoustic level	45 dBA
Heat dissipation	67.6 Btu/h
Show note OP temperature	No

Batteries & Runtime

Battery type	Lead-Acid battery
Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	16 h
RBC Quantity	1

Liquid Electrolyte Value	0
Battery curve	C
Battery Charge Power (Watts)	11 W rated
Battery power in VAH	172 VAh capacity 172 VAh runtime
Extendable Run Time	0

Communications & Management

Control panel	Multi-function LCD status and control console
Audible Alarm	Alarm when on battery : distinctive low battery alarm : overload continuous tone alarm

Surge Protection and Filtering

Surge energy rating	789 J
Filtering	Full time multi-pole noise filtering :5% of IEEE surge let-through : zero clamping response time: in
Data line protection	Network line - 10/100/1000 Base-T Ethernet (RJ45 connector) Coaxial cable for CATV/SATV/modem/Audio-Video (coax connector)





Ordering and shipping details

GTIN	00731304331780
Package weight(Lbs)	28.00 lb(US) (12.7 kg)

Packing Units

Package 1 Height	13.70 in (34.8 cm)
Package 1 width	8.94 in (22.7 cm)
Package 1 Length	19.33 in (49.1 cm)
SCC14	10731304331787
Number of Units in Package 3	32

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Energy Star	 ENERGY STAR UPS V1.0 (USA)
REACH Regulation	 REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
Optimized Energy Efficiency	Energy efficient product

Contractual warranty

Warranty	3 years repair or replace
----------	---------------------------