# **AP4450**

Rack ATS, 100/120V, 15A, 5-15 in, (10) 5-15R out





#### Overview

Lead time	Usually in Stock
-----------	------------------



#### General

Provided equipment	Mounting Hardware	
	Rack Mounting brackets	
	Serial configuration cable	

### Physical

•		
Cable length	8 ft (2.44 m)	
Color	Black	
Depth	9.29 in (23.6 cm)	
Height	1.73 in (4.4 cm)	
Net Weight	9.70 lb(US) (4.4 kg)	
Maximum Width	17.01 in (43.2 cm)	

#### Input

Input Frequency	50/60 Hz	
Line Rated Current	12 A	
Plug standard	NEMA 5-15P	
Input current limits	15 A	
Load Capacity	1440 VA	
Nominal Input Voltage	100 V 120 V	

#### Output

Maximum Total Current Draw per Phase	15 A
Number of power socket outlets	10 NEMA 5-15R
Output voltage	100 V 120 V

### Conformance

Product certifications	PSE TÜV-C TÜV-NURTL VCCI Class A	
Standards	FCC Part 15 class A ICES-003	

### Environmental

Ambient air temperature for operation	23113 °F (-545 °C)
Relative humidity	095 %
Operating altitude	010000 ft
Ambient air temperature for storage	-13149 °F (-2565 °C)
Storage altitude	050000 ft (0.0015240.00 m)

# Ordering and shipping details

GTIN	00731304333494
Package weight(Lbs)	13.60 lb(US) (6.17 kg)

# Packing Units

Package 1 Height	4.49 in (11.4 cm)
Package 1 width	23.62 in (60 cm)
Package 1 Length	14.02 in (35.6 cm)

### Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
EU RoHS Directive	Compliant	
Lead free	Yes	
Mercury free	Yes	
RoHS exemption information	₫Yes	
Halogen content performance	Halogen free product	

### Contractual warranty

	•
Warranty	2 years repair or replace