



## Overview

Presentation	Free up space and secure power cords between rack-mount PDUs and attached IT equipment with this exclusive easy-to-use cord retention method. While these cords will fit into any standard IEC receptacle or power inlet; the "locking" feature is enabled only when used with APC AP8000 series Rack PDUs or IT equipment with built-in locking receptacles. These locking connectors reduce the probability of accidentally disconnecting cords and dropping loads.
Lead time	Usually in Stock

## Physical

Cable length	6 ft (1.83 m)
Color	Black
Depth	2.76 in (7 cm)
Height	11.81 in (30 cm)
Net Weight	4.76 lb(US) (2.16 kg)
Maximum Width	3.15 in (8 cm)

## Input

Plug standard	IEC 60320 C20
Number of cables	6
Max line current	16 A
Input current limits	16 A

## Output

Maximum Total Current Draw per Phase	16 A
Number of power socket outlets	1 IEC 60320 C19
Cord Length	6 ft (1.83 m)

## Conformance

Product certifications	CCC CSA PSE UL Listed VDE
------------------------	---------------------------------------

## Environmental

Ambient air temperature for operation	32...167 °F (0...75 °C)
Relative humidity	20...80 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-13...167 °F (-25...75 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)

## Ordering and shipping details

Category	11309 - APC RESALE PRODUCTS
GTIN	00731304279723
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	No
Country of origin	CN

## Packing Units

Package 1 Height	11.81 in (30 cm)
Package 1 width	3.15 in (8 cm)
Package 1 Length	2.76 in (7 cm)
SCC14	10731304279720
Number of Units in Package 3	240

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Lead free	Yes
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Halogen content performance	Halogen free product

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------