



Overview

Lead time	Usually in Stock
-----------	------------------

General

Provided equipment	All required connectors Battery recycling guide Installation guide Reusable packaging
--------------------	--

Physical

Depth	5.91 in (15 cm)
Height	4.25 in (10.8 cm)
Net Weight	13.25 lb(US) (6.01 kg)
Maximum Width	5.20 in (13.2 cm)

Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Operating altitude	0...10000 ft
Relative humidity	0...95 %
Ambient air temperature for storage	5...113 °F (-15...45 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)

Batteries & Runtime

Battery blocks per string	2
Battery Slots Empty	0
Included Battery Modules	0
Device mounting	Stand alone battery stack
Battery voltage	24 V
Battery type	Lead-Acid battery
RBC Quantity	1

Ordering and shipping details

Package weight(Lbs)	15.45 lb(US) (7.01 kg)
---------------------	------------------------

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

Package 1 Height	7.99 in (20.3 cm)
Package 1 width	6.61 in (16.8 cm)
Package 1 Length	8.82 in (22.4 cm)
SCC14	10731304291975
Number of Units in Package 3	75

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Energy Star	ENERGY STAR UPS V1.0 (USA)
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	1 year repair or replace
----------	--------------------------