



Overview

Presentation	The NetBotz Rack Monitor 750 provides integrated surveillance, sensing, access control, and advanced alerting for IT environments of all sizes, from single-rack edge networks to large data centers.
Lead time	Usually in Stock



General

Provided equipment	Rack Mounting brackets Temperature/Humidity Sensor USB cable
Camera Frame Rate	Up to 30fps
Product compatibility	Rack Sensor Pod 150 Room Sensor Pod 155
Display resolution	Up to 1280x1024
APC Universal Sensors Supported	0-5V Door contact Dry Contact Humidity Smoke Fluid Spot Leak Temperature Vibration
Number of Universal Sensor Ports	6
Number of Sensor Pods Supported	12
Number of Universal Sensors Supported	78
Number of Cameras Supported	4

Physical

Color	Black
Depth	7.01 in (17.8 cm)
Height	1.69 in (4.3 cm)
Mounting location	Front Rear
Net Weight	5.40 lb(US) (2.45 kg)
Maximum Width	17.01 in (43.2 cm)
Mounting position	Horizontal

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Conformance

Standards	CSA C22.2 No. 60950-1-03 FCC Part 15 class A ICES-003 UL 60950-1
Product certifications	2014/30/EU AS/NZS 3548 (C-Tick) Class A CE EMC Directive 2004/108/EC VCCI Class A

Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Operating altitude	0...10000 ft
Relative humidity	0...95 %
Ambient air temperature for storage	5...149 °F (-15...65 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)

Communications & Management

Communication network type	RJ-45 10/100/1000 Base-T
Communication port protocol	A-Link DHCP HTTPS IPv4 SNMP v1 SNMP v3 SSH v2 TCP/IP

Ordering and shipping details

Package weight(Lbs)	9.19 lb(US) (4.17 kg)
---------------------	-----------------------

Packing Units

Package 1 Height	4.76 in (12.1 cm)
Package 1 width	20.98 in (53.3 cm)
Package 1 Length	12.52 in (31.8 cm)

Offer Sustainability

EU RoHS Directive	Under investigation
-------------------	---------------------