



Overview

Lead time	Usually in Stock
-----------	------------------



General

Provided equipment	All required connectors Battery recycling guide Installation guide Reusable packaging
--------------------	--

Physical

Color	Black
Depth	6.02 in (15.3 cm)
Height	3.94 in (10 cm)
Net Weight	3.20 lb(US) (1.45 kg)
Maximum Width	2.09 in (5.3 cm)

Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Operating altitude	0...10000 ft
Relative humidity	0...95 %
Ambient air temperature for storage	23...113 °F (-5...45 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)
Storage Relative Humidity	0...95 %

Batteries & Runtime

Battery Placement	Internal Battery
Battery Slots Empty	0
Included Battery Modules	0
Device mounting	Enclosed battery cartridge
Battery voltage	16 V
Battery type	Lead-Acid battery
RBC Quantity	1

Ordering and shipping details

GTIN	00731304264385
Package weight(Lbs)	3.75 lb(US) (1.7 kg)

Packing Units

Package 1 Height	7.01 in (17.8 cm)
Package 1 width	3.35 in (8.5 cm)
Package 1 Length	8.27 in (21 cm)
SCC14	10731304264382
Number of Units in Package 3	240

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
Energy Star	ENERGY STAR UPS V1.0 (USA)
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Warranty	1 year repair or replace
----------	--------------------------