



### Overview

Lead time	Usually in Stock
-----------	------------------

### Physical

Cable length	6 ft (1.83 m)
Color	Black
Depth	12.99 in (33 cm)
Height	1.26 in (3.2 cm)
Net Weight	2.03 lb(US) (0.92 kg)
Maximum Width	3.50 in (8.9 cm)

### Input

Input Frequency	50/60 Hz
Plug standard	NEMA 5-15P
Switching current capacity	15 A
Nominal Input Voltage	120 V

### Output

Number of power socket outlets	8
Outlet standard	NEMA 5-15R

### Conformance

UL 1449 TVSS Rating	L-N: 400 L-G: 500 N-G: 500
Product certifications	CSA NOM
Standards	UL 1363 UL 1449
Equipment protection policy	Lifetime : \$150000

### Environmental

Ambient air temperature for operation	32...113 °F (0...45 °C)
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	5...113 °F (-15...45 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)

## Surge Protection and Filtering

Data Lines Protected (multi-line only)	1-4
NM Surge Response Time (ns)	0 ns common mode
Common mode rejection	70 dB
Surge energy rating	2770 J
Data line protection	RJ11 2-Way Modem/Fax/DSL splitter with protection (four wire dual lines)

## Ordering and shipping details

GTIN	00731304249054
Package weight(Lbs)	2.43 lb(US) (1.1 kg)

## Packing Units

Package 1 Height	2.36 in (6 cm)
Package 1 width	5.59 in (14.2 cm)
Package 1 Length	14.17 in (36 cm)
SCC14	10731304249051
Number of Units in Package 2	6
Package 2 Weight	16.5 lb(US) (7.48 kg)
Package 2 Height	12 in (304.80 mm)
Package 2 width	8 in (203.20 mm)
Package 2 Length	15 in (381.00 mm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: 1,3-Butadiene, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>

## Contractual warranty

Warranty	Lifetime
----------	----------