



### Main

Marketing Trade Name	QO
Product	Load Center
Cover Type	Surface cover

### Complementary

Tightening Torque	Main lugs 50 lb.in, AWG 6...AWG 2/0, aluminium/copper
Load Center Type	Main lugs
Rated Current	125 A
Number of Spaces	4
Max Short Circuit Current Rating	10 kA
Maximum Number of Single Pole Circuits	8
Maximum Number of Tandem Breakers	4
Number of Phases	1 phase
Voltage Rating	120/240 V AC
Wire Size	AWG 12...AWG 2/0 aluminium AWG 14...AWG 2/0 copper
Electrical Connection	Lugs
Grounding Bar	Grounding bar included (not installed)
Electrical Connection	Lugs
Wiring Configuration	3-wire
Busbar Material	Tin plated copper busbar
Enclosure Material	Welded sheet steel
Cover Finish	Baked enamel Gray
Box Number	21
Height	14.80 in (376 mm)
Width	8.90 in (226 mm)

### Environment

Enclosure Rating	NEMA 1 indoor
Ambient Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)
Product Certifications	UL Listed

### Ordering and shipping details

Category	00101 - QO 1PH LC,2-8CKT,NEMA 1,3R
Discount Schedule	DE3A
GTIN	00785901484400
Nbr. of units in pkg.	1
Package weight(Lbs)	9.98 lb(US) (4.53 kg)

Returnability	Yes
Country of origin	MX

### Packing Units

Package 1 Height	4.30 in (10.922 cm)
Package 1 width	10.60 in (26.924 cm)
Package 1 Length	16.60 in (42.164 cm)

### Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

### Contractual warranty

Warranty	18 months
----------	-----------