# QO612L100DS

# LOAD Center QO MLO 240V 100A 1PH 6SP N1





#### Main

TTT CALL		
Marketing Trade Name	QO	
Product	Load Center	
Cover Type	Surface cover with door	

#### Complementary

Tightening Torque	Main lugs 50 lb.in, AWG 8, aluminium/copper Main lugs 50 lb.in, AWG 6AWG 1/0, aluminium/copper	
Load Center Type	Main lugs	
Rated Current	100 A	
Number of Spaces	6	
Max Short Circuit Current Rating	10 kA	
Maximum Number of Single Pole Circuits	12	
Maximum Number of Tandem Breakers	6	
Number of Phases	1 phase	
Voltage Rating	120/240 V AC	
Wire Size	AWG 8AWG 1 aluminium/copper	
Electrical Connection	Lugs	
Grounding Bar	Grounding bar (ordered separately)	
Electrical Connection	Lugs	
Wiring Configuration	3-wire	
Busbar Material	Tin plated aluminium busbar	
Enclosure Material	Welded sheet steel	
Cover Finish	Baked enamel Gray	
Box Number	4	
Height	12.56 in (319 mm)	
Width	8.90 in (226 mm)	

#### **Environment**

Enclosure Rating	NEMA 1 indoor
Ambient Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)
Product Certifications	UL Listed

### Ordering and shipping details

Category	00101 - QO 1PH LC,2-8CKT,NEMA 1,3R	
Discount Schedule	DE3A	
GTIN	00785901785620	
Nbr. of units in pkg.	1	
Package weight(Lbs)	8.25 lb(US) (3.74 kg)	

Returnability	Yes
Country of origin	MX
Packing Units	
Unit Type of Package 1	PCE
Package 1 Height	14.40 in (36.576 cm)
Package 1 width	4.40 in (11.176 cm)
Package 1 Length	10.70 in (27.178 cm)
Package 2 Weight	671.00 lb(US) (304.36 kg)
Offer Sustainability	
Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	₽¥Yes
China RoHS Regulation	<b>☑</b> China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

## Contractual warranty

Warranty	18 months