2195852-1 <

TE Internal #: 2195852-1 Antenna, LTE / GNSS / 4G, Printed Circuit Board, Mounting Hole, Tab Mount

View on TE.com >



Antennas



Wireless Application: 4G, GNSS, LTE

Mounts To: Printed Circuit Board

Mounting Retention Type: Mounting Hole

Antenna Connection Type: Tab Mount

Application by Region: GNSS - Global - 1559 – 1606 MHz, LTE All Band - 1710 – 2700 MHz, LTE All Band - 698 – 960 MHz, Wi-Fi -

Global - 2400 – 2483.5 MHz

Features

Product Type Features

Antenna Connection Type	Tab Mount
Configuration Features	
Band Type	6 band
Antenna Protocol	LTE World Band
Number of Ports	1
Antenna Style	Embedded
Antenna Type	PCB
Electrical Characteristics	
VSWR (Max)	<3:1
Impedance	50 Ω
Active Antenna	No
Signal Characteristics	
Frequency Band	1420 – 1630 MHz, 1710 – 2700 MHz, 3200 – 3800 MHz, 4400 – 5000 MHz, 5150 – 5875 MHz, 698 – 960 MHz

2195852-1

Antenna, LTE / GNSS / 4G, Printed Circuit Board, Mounting Hole, Tab Mount



Gain (Max)	4.5 dB
Body Features	
Product Weight	3.5 g[.123 oz]
Mechanical Attachment	
Region	Global
Polarization	Linear
Mounts To	Printed Circuit Board
Mounting Retention Type	Mounting Hole
Dimensions	
Product Length	50 mm[2.16 in]
Product Width	20 mm[.787 in]
Product Height	1.58 mm[.062 in]
Usage Conditions	
Application by Region	GNSS - Global - 1559 – 1606 MHz, LTE All Band - 1710 – 2700 MHz, LTE All Band - 698 – 960 MHz, Wi-Fi - Global - 2400 – 2483.5 MHz

Operation/Application

Wireless Standard	LTE, UMTS, US Dual, EU Triband & WCDMA
Industry Standards	
Wireless Application	4G, GNSS, LTE
Packaging Features	
Packaging Method	Bag & Box
Other	
Precision Level	Standard
Product Compliance For compliance documentation, visit the product page on TE.com>	
EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	

2195852-1

Antenna, LTE / GNSS / 4G, Printed Circuit Board, Mounting Hole, Tab Mount



Current ECHA Candidate List: JAN 2021 (211) Candidate List Declared Against: JUN 2020 (209) SVHC > Threshold: Not Yet Reviewed

Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free

Halogen Content

Solder Process Capability

Hand solderable with lead free solder

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Customers Also Bought



2195852-1

Antenna, LTE / GNSS / 4G, Printed Circuit Board, Mounting Hole, Tab Mount





Documents

Product Drawings

PCB ANT, TAB MOUNT, 698-5875MHz, 55X20mm

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_2195852-1_1.2d_dxf.zip

English

Customer View Model

ENG_CVM_CVM_2195852-1_1.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_2195852-1_1.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages PCB Ant, 5G-2G, CAT-M, WORLD BAND

English