




Datasheet

Tin Plated Crimp Ring Terminal

RS Stock number [534-575](#)



ENGLISH

| Insulated Stock no. | Wire range | | Colour | Dimensions | | | | Stud size | |
|---------------------|------------|-----------------|--------|------------|-----|------|-----|-----------|-----|
| | AWG | mm ² | | B | D | L | I | AWG | mm |
| 534238 | 22-16 | 0.5-1.5 | Red | 5.5 | 4.3 | 16.0 | 9.9 | 4 | 3.2 |
| 534222 | 22-16 | 0.5-1.5 | Red | 6.6 | 4.3 | 18.7 | 9.9 | 6 | 3.7 |
| 534216 | 22-16 | 0.5-1.5 | Red | 6.0 | 4.3 | 20.0 | 9.9 | 8 | 4.3 |
| 534200 | 22-16 | 0.5-1.5 | Red | 8.0 | 4.3 | 20.5 | 9.9 | 10 | 5.3 |
| 534193 | 22-16 | 0.5-1.5 | Red | 11.0 | 4.3 | 25.5 | 9.9 | 1 / 4 | 6.4 |
| 2082492 | 22-16 | 0.5-1.5 | Red | 12.0 | 4.3 | 27.0 | 9.5 | 5/16 | 8.4 |

| Stock no. | AWG | mm ² | Colour | B | D | L | I | AWG | mm |
|-----------|-------|-----------------|--------|------|-----|------|-----|-------|-----|
| 534597 | 16-14 | 1.5-2.5 | Blue | 6.7 | 4.8 | 19.0 | 9.9 | 6 | 3.7 |
| 534581 | 16-14 | 1.5-2.5 | Blue | 8.0 | 4.8 | 20.5 | 9.9 | 8 | 4.3 |
| 534575 | 16-14 | 1.5-2.5 | Blue | 9.5 | 4.8 | 22.0 | 9.9 | 10 | 5.3 |
| 534569 | 16-14 | 1.5-2.5 | Blue | 10.5 | 4.8 | 26.0 | 9.9 | 1 / 4 | 6.4 |
| 2082509 | 16-14 | 1.5-2.5 | Blue | 12.0 | 4.8 | 27.5 | 9.9 | 5/16 | 8.4 |

| Stock no. | AWG | mm ² | Colour | B | D | L | I | AWG | mm |
|-----------|-------|-----------------|--------|------|-----|------|------|-------|------|
| 534468 | 12-10 | 2.5-6.0 | Yellow | 7.2 | 6.5 | 27.0 | 13.5 | 6 | 3.7 |
| 534452 | 12-10 | 2.5-6.0 | Yellow | 9.5 | 6.5 | 26.5 | 13.5 | 8 | 4.3 |
| 534446 | 12-10 | 2.5-6.0 | Yellow | 9.5 | 6.5 | 27.0 | 13.5 | 10 | 5.3 |
| 534430 | 12-10 | 2.5-6.0 | Yellow | 11.0 | 6.5 | 29.0 | 13.5 | 1 / 4 | 6.4 |
| 534424 | 12-10 | 2.5-6.0 | Yellow | 14.0 | 6.5 | 34.0 | 13.5 | 5/16 | 8.4 |
| 2082537 | 12-10 | 2.5-6.0 | Yellow | 15.0 | 6.5 | 35.5 | 13.5 | 3/8 | 10.0 |