



Overview

Lead time	Special Order - Call for Quoted Lead Times
-----------	--

General

Provided equipment	Installation guide User Manual
--------------------	-----------------------------------

Physical

Cable length	3 ft (0.91 m)
Color	Black
Depth	25.98 in (66 cm)
Height	17.01 in (43.2 cm)
Net Weight	125.27 lb(US) (56.82 kg)
Width	5.12 in (13 cm)

Input

Permissible voltage	180...264 V
Input current limits	30 A
Load Capacity	4800 VA
Input Frequency	50/60 Hz
Plug standard	NEMA L6-30P
Nominal Input Voltage	208 V 240 V

Output

Maximum Total Current Draw per Phase	30 A
Protection type	Circuit breaker
Number of power socket outlets	8 NEMA 5-20R 2 NEMA L6-20R 1 NEMA L6-30R 1 NEMA L14-30R
Output voltage	120 V 208 V

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environmental

Ambient air temperature for operation	32...104 °F (0...40 °C)
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-13...149 °F (-25...65 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)




Ordering and shipping details

Package weight(Lbs)	140.30 lb(US) (63.64 kg)
---------------------	--------------------------

Packing Units

Package 1 Height	13.66 in (34.7 cm)
Package 1 width	23.74 in (60.3 cm)
Package 1 Length	38.58 in (98 cm)
SCC14	10731304217807
Number of Units in Package 3	6

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	 REACH Declaration
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	 Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------